

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6						5							4											3
D																									2
E																									1
F																									
G	1																								12
H																									
J																									
K																									
L	18																								13
M																									
N																									
O																									
P																									
Q	19																								24
R																									
S																									
T	30																								25
U																									
V																									
W																									
X	31																								36
Y																									
Z																									

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

 CORNER MONUMENT       WITNESS MONUMENT

BEARINGS ARE BASED ON: \_\_\_\_\_

OBSERVATION SHEET 581

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE R-1(1)

NE581

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT (SEPT)

PG 9 NORTH ON EAST SIDE SECTION 25

- 792 LEAVE MARSH
- 2640 SET QUARTER SECTION POST BLACK OAK 12 S21W 81.84'; BLACK OAK 20 N40W 94.38'
- 5280 SET POST CORNER SECTIONS 24 & 25 BUR OAK 10 N7W 33.66'; BUR OAK 8 S12W 91.08. LAND SAME AS LAST MILE

PG 10 NORTH ON EAST SIDE SECTION 24

- 1150.38 BUR OAK 10 IN DIA
  - 2640 SET QUARTER SECTION POST BUR OAK 8 S68W 7.92'; BUR OAK 10 N29W 82.5'
  - 5280 SET POST CORNER SECTIONS 13 & 24 BUR OAK 14 S33W 64.02'; BUR OAK 16 N12W 34.98'
- LAND ROLLING SECOND RATE THICKLY TIMBERED WITH BUR WHITE AND BLACK OAK RED ROOT ROSE WILLOW

1834 HARRISON (JANUARY) AVON TWP PG 41 EAST RANDOM BETWEEN 24 & 25

- 2640 LEAVE MARSH & SET TEMPY 1/4 POST
  - 5306.4 INT. E BDY 59.4' NORTH OF POST LAND 1ST 1/2 MILE & WET 3RD RATE 2ND 1/2 BDG 2ND RATE WITH BUR OAK TIMBER
- WEST CORRECTED BETWEEN SECS 24 & 25
- 2653.2 QUARTER SEC COR BUR OAK 12 S10E 9.9'; BUR OAK 10 S52W ??
  - 5306.4 SEC COR

1834 MILLER (MARCH) PG 33 WEST RANDOM BETWEEN SECS 19 & 30

- 5243.7 INTERSECT RANGE LINE 36.96' SOUTH POST
- LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY OAK & HAZEL U.G. (UNDER GROWTH)
- EAST CORRECTED BETWEEN SEC 19 & 30
- SET POST COR OF 19 & 30 BUR OAK 14 IN S27E 32.34'; BUR OAK 14 IN N37E 79.86

- 87.12 BUR OAK 15 IN DIA
- 792 WHITE OAK 15 IN DIA
- 2593.8 BUR OAK 12 IN DIA
- 2603.7 SET 1/4 SEC POST BUR OAK N73E 9.9'; BUR OAK 16 S29W 15.18'
- 2947.56 BUR OAK 18 IN
- 4979.7 BUR OAK 10 IN
- 5243.7 SEC COR

1870 RUGER VOL 2 PG 42 FD OLD STAKE & STUMPS OF BEARING TREES. SET HH 34X11X7 SURROUNDED BY 4 LIMESTONES. VAR 5-26 2609.31 TO S 1/4 COR SEC 19, VAR 6-50 2680.92 TO W 1/4 COR SEC 19.

1870 RUGER VOL 2 PG 48 SEE PLAT OF SEC 19 NEWARK PG 42. VAR 6-13 2677.29' TO S 1/4 COR SEC 24 AVON TWP.

1871 COLLIN'S REMONUMENTATION NOTES

PG 203 NORTH ON WEST LINE OF 19 VARIATION 6

- 2674.32 SET 1/4 STONE IN PLACE OF STONE SET BY RUGER AGREEING WITH ROOTS OF WITNESS TREES. NOV 3RD 1871

CONTINUED NORTH VARIATION 6-30

- 5346 INTERSECT SECTION LINE 6.6' WEST OF CORNER. SET STONE FOR CORNER OF 18 & 19 IN PLACE OF STONE SET BY RUGER. CORRECTED VARIATION 6-39

PG 202 EAST BETWEEN 19 & 30 VARIATION 5-20

- 2608.98 SET 1/4 STONE IN PLACE OF STONE SET BY RUGER AGREEING WITH WITNESS TREE.

CONTINUED EAST VARIATION 4-30

*Donald Barnes*

7-09-D1

NE581

5254.26 SECTION CORNER

PG 201 NORTH ON WEST LINE OF 30 VARIATION 6

2678.94 SET 1/4 STONE BY STUMPS OF WITNESS TREES CONTINUED  
NORTH SAME VARIATION

5347.98 SET STONE FOR CORNER OF 19 & 30 IN PLACE OF STONE SET  
BY RUGER. AGREEING WITH STUMPS OF WITNESS TREE.

1962 BATTERMAN VOL 4 PG 128 FD 34X11X7 STONE AT SW COR SEC 19.  
REFERENCED SAME.

1979 BARNES VOL 5 PG 553 TIES DESTROYED DUG & FD CUT LIMESTONE 2'  
DEEP. SET ALUM. MON.

1993 KREBS CSM 16 PG 234 2669.06 TO W 1/4 COR SEC 30, 1287.35 TO N 1/16TH  
COR OF NW 1/4 SEC 30, AN ANGLE OF 88-58-41 @ NW COR SEC 30 FROM  
NORTH LINE TO WEST LINE OF SEC 30

1995 BARNES R-1 COORDINATES WERE SUPPLIED BY WPL. THE SURVEY  
WAS BY GPS & CONNECTED TO THREE ROCK COUNTY GPS CONTROL  
MONUMENTS; BRODHEAD (305S), AVON (312S), & NEWARK EAST (313S)  
NAD83(91) 193,179.965; 2,171,235.250

FD ALUM. MON. 0.15' DEEP & 3.5' NORTH OF CENTER OF PVMT. FD TIES  
FROM VOL 5 PG 553.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found  
perpetuated location?

ACCEPTED FD L.S. AS NW COR SEC 30.

D) Describe any material discrepancy between the location of the corner as restored or reestablished  
and the location of that corner as previously restored or reestablished by distance and direction. Show  
the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as  
previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least  
4 of the witness monuments shown on the drawing in (a), above.

THE ORIGINAL GOV. SURVEYORS, MILLER & MULLETT EACH SET A POST.  
ONE FOR THE CLOSING CORNER FOR NW COR OF SEC 30 NEWARK AND THE  
OTHER THE STANDARD CORNER FOR THE TOWNSHIP LINE. DURING MARCH  
OF 1833, HARRISON SURVEYED AVON TWP SOUTH OF SUGAR RIVER & IN  
JANUARY OF 1834, HE SURVEYED THE TWP NORTH OF SUGAR RIVER. HE  
ALSO HAD A SPECIAL CONTRACT TO SURVEY THE SOUTH LINE OF SEC 36  
AVON TWP, WHICH HE DID IN 1834. IN THE 1834 SURVEY HE NOTES WHILE  
SURVEYING THE NORTH LINE OF SEC 36 HE "INT. THE EAST BOUNDARY IN  
MARSH 924' ". IS THE "924'" THE DISTANCE TO THE RANDOM STATE LINE?  
LATER THAT SPRING, MILLER SURVEYED NEWARK TWP. IN THE  
TOWNSHIPS TO THE NORTH, STANDARD AND CLOSING CORNERS ON THIS  
LINE ARE DOCUMENTED AND PERPETUATED. MILLER'S FIELD NOTES  
STATE HE SET POSTS & BEARING TREES WHERE HE CLOSED ON THE  
AVON/NEWARK TOWN LINE FROM THE STATE LINE TO THE NW CORNER OF  
SEC 19. SINCE COLLIN ACCEPTED BEARING TREE EVIDENCE AT THE 1/4  
CORNERS ALONG THE TOWN LINE FROM THE SW COR SEC 31 TO THE NW  
COR SEC 19, HE MUST OF CONSIDERED THE AVON AND NEWARK CORNERS  
TO BE COMMON. SINCE THE ORIGINAL GOV. SURVEYORS SET STANDARD  
AND CLOSING CORNERS ON THIS LINE, DID COLLIN USE THE BEARING  
TREES AT THE CLOSING CORNERS FOR NEWARK OR AVON TOWNSHIP? HIS  
MEASUREMENTS SUPPORTS THE NOTION THAT HE USED MULLETT'S  
CORNERS.

*Ronald Barnes*  
7-09-01

SHEET 2 OF 3 CORNER CODE R-1(1)

NE5B1

*(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.*

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal  
Donald Barnes  
7-09-01  
emboss

SHEET 3 OF 3

CORNER CODE **R-1(1)**

A-E 7.08 REQUIREMENT