

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6				5				4					3					2					1
C																								
D																								
E																								
F																								
G	1																							
H																								
I																								
J																								
K																								
L	18																							
M																								
N																								
O																								
P	19																							
Q																								
R																								
S																								
T	30																							
U																								
V																								
W																								
X	31																							
Y																								
Z																								

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

Fd TIES IN VOL 9 PG 143

OBSERVATION sheet 466

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE P13(1)

NE577

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 21 NORTH BETWEEN SECS 21 & 22
 - 782.1 BUR OAK 18 IN DIAMETER
 - 1797.84 SPRING BROOK C S.E. 1.32 WIDE
 - 2241.36 BUR OAK 20 IN
 - 2640 SET 1/4 SEC. POST BUR OAK 20 IN S24E 29.7'; BUR OAK 20 IN N82W 14.52'
 - 2772 ENTER MARSH C S.E.
 - 3305.28 BROOK 1.32' S.W
 - 4422 LEAVE MARSH
 - 4923.6 BUR OAK 20 IN
 - 5280 SET POST COR OF SEC 14,15,21,22 BUR OAK 16 S49E 31.68'; BUR OAK 20 N51W 38.94. LAND MOSTLY 2ND RATE LEVEL

- 1871 COLLINS REMONUMENTATION NOTES
 - PG 166 NORTH BETWEEN 21 & 22 VARIATION 5
 - 2648.58 INTERSECT 1/4 LINE 9.9' WEST OF CORNER. SET 1/4 STONE BY STUMPS OF WITNESS TREES CORRECTED VARIATION 5-14
CONTINUED NORTH VARIATION 5
 - 5311.68 SET STONE FOR COR ER OF 15,16,21,22 BY WITNESS TREE AND STUMP
- 1976 BARNES VOL 5 PG 143 FD CUT STONE 0.5' ABOVE GROUND MARKED S 1/4 @ FENCE INT. REFERENCED SAME.
- 1976 BARNES VOL 5 PG 144 2663.10 TO NE COR SEC 21
- 1992 COMBS CSM 16 PG 31 1315.22 WEST TO 1/16TH COR
- 1994 COMBS CSM 18 PG 331 2650.76 TO SW COR SEC 2 & ANGLE OF 177-45-05 @ SW COR SEC 22 FROM W 1/4 COR SEC 22 TO W 1/4 COR SEC 27
- 1995 BARNES P-13 COORDINATES WERE SUPPLIED BY WPL. THE SURVEY WAS BY GPS & CONNECTED TO THREE ROCK COUNTY GPS CONTROL MONUMENTS; BRODHEAD (305S), AVON (312S), & NEWARK EAST (313S) NAD83(91) N/S 195,722.006; E/W 2,187,156.264. I CONVERTED THOSE TO COUNTY AND USED AS CONTROL IN ADJUSTMENT PROGRAM. COUNTY N/S 448,580.189; E/W 214,907.04

FD CUT LIMESTONE 1' ABOVE GROUND @ FENCE INT. PLACED CARSONITE POST ON SIDE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CUT LIMESTONE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal
Donald
Barnes
emboss

Number of included sheets 1

6-29-01

CORNER CODE P-13(1)