

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N., R. 11 E

CORNER CODE INDEX

PORTER TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	1																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T																									
U	30																								
V																									
W																									
X	31																								
Y																									
Z																									

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE E 19

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON EAST ON RAND. BET. 2 & 11
 274.56 LEAVE CAT-FISH. SET MEAND. POST
 2640 TEMPY 1/4 POST
 3828 ENTER PRAIRIE
 4264.92 TRAIL CR6 N.W.
 5207.4 TRAIL N.W.
 5339.4 INT. E BDY 19.8' SOUTH OF POST
 LAND 1ST 1/2 MILE SAME AS BEFORE. LAST 1/2 LEVEL 1ST
 RATE PRAIRIE
 WEST COR. WEST
 2669.7 QUARTER SEC. COR. {BURR OAK 12" N70W 91.08'; BURR
 OAK 12" S47E 137.28' BURR OAK 12; BURR OAK 12}
 MARKED
 5339.4 SEC COR. OCT 31, 1833 .
 1886 RUGER VOL 2 PG 282 FOUND STUMP OF S.E. B.T & WHERE STUMP
 OF N.W.B.T. HAD BEEN DUG UP. COR. FENCE POST CORRECT
 SURROUNDED IT WITH LOT OF H.H. STONES. VAR 5-7(?)2
 2628.78 TO CENTER OF SEC 11, 2707.32 VAR 6-34 TO NE COR
 SEC 11; EASTERLY 1111.6' TO STAKE SURROUNDED BY 3 HH
 STONES ON NORTH LINE OF NE 1/4 SEC 11. CENTER OF SEC IS
 2692.47 FROM W 1/4 COR SEC 11 AND 2743.95 FROM E 1/4 COR
 SEC 11.

FOUND LARGE ROTTED WOOD POST SURROUNDED BY STONES THAT IS
 IN HARMONY WITH CENTER OF SEC 11 AND NE COR SEC 11. SET POLY.
 MON. & CARSONITE POST.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

NUMBER OF INCLUDED SHEETS 2

Emboss
 Donald Barnes
 6-14-01

CORNER CODE **E-19**

A-E 7.08 REQUIREMENT



CENTER?

326,134.04 N/S
456,027.94 E/W

FD LARGE NAIL
0.2' DEEP
@ CENTER OF PVMT
& DN LINE N/S
FENCE
DID NOT ACCEPT NOR
REJECT AS CENTER OF
SEC 2

SEC 2
SEC 2

**NW
COR**

**N 1/4
COR**

323516.96 N/S
456041.89 E/W N89-27-18E 2708.63 323,542.73 N/S
PRO 2709.46 458,750.40 E/W

1886 RUGER VAR 6-34 2707.32
1833 HARRISON 2669.70

NE COR

1833 HARRISON 2640

PRO IS THE VALUE COMPUTED
FROM THE FOLLOWING RECORD
& MEASURED DISTANCES.

RUGER	MEASURED
5436.42	5441.06
2722.50	2725.72
2722.50	2723.47
2753.52	2755.88
2578.83	2580.69
2707.32	2708.63
2628.78	2631.43
TOTAL	21,549.87
	21,566.88

FD L.S.
SET POLY. MON.
& CARSONITE

COUNTY COORDINATES

N88-23-37E 5441.06
1886 RUGER 5436.42
N88-23-26E 2746.14
PRO 2746.12
1886 RUGER 2743.95

FD ALUM.

1833 HARRISON 2640
1886 RUGER VAR 6-30 2578.83
N1-21-35W 2580.69
PRO 2580.86

320,962.77 N/S
458,811.64 E/W

**E 1/4
COR**

FD CONC.
MON.

**W 1/4
COR**

320,810.23 N/S
453,372.71 E/W

N88-23-47E 2694.93
PRO 2694.60
1886 RUGER 2692.47
1886 RUGER VAR 6-35

320885.64 N/S
456066.58 E/W

CENTER

PORTER TWP
TAN R11E

FD TIES

1833 HARRISON 2640
1886 RUGER VAR 5-35 2753.52
N0-01-47W 2755.93
1991 BARNES N0-09-02W 2755.88
PRO 2755.69

NO-03-33E 2657.17

SEC 11
SEC 11

USED 1991
OBSERVATIONS
(FD ALUM.)

318,179.69
456,095.55 E/W

SW COR

USED 1991
OBSERVATIONS
(FD R/R)

1833 HARRISON 2692.80
1886 RUGER VAR 5-847 2722.50
1991 BARNES N89-33-35E 2725.70
N89-26-25E 2725.72
PRO 2724.65

**S 1/4
COR**

1833 HARRISON 2640
1886 RUGER VAR 5-847 2722.50
1991 BARNES N89-32-55E 2723.42
N89-25-39E 2723.47
PRO 2724.65

SE COR

FD PIPE
318,206.90 N/S
458,818.88 E/W

Donald Barnes
6-14-01

3 OF 3

E-19