

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

T. 4 N. R. 10 E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																											A
B																											B
C																											C
D																											D
E																											E
F																											F
G																											G
H																											H
J																											J
K																											K
L																											L
M																											M
N																											N
O																											O
P																											P
Q																											Q
R																											R
S																											S
T																											T
U																											U
V																											V
W																											W
X																											X
Y																											Y
Z																											Z
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

PORTER TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE P-9

PO576

W1/4CORSEC21

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON (NOV) T4N R11E 4TH MER. NORTH

BET. 20 & 21

2640.0 QUARTER SEC COR. BURR OAK 24 S73W 15.84'; BURR OAK 12 N73E 43.56'J
BURR OAK 24; BURR OAK 12}MARKED
5280.0 SET COR TO SECS 16,17,20,21 IN ?? SOUTHERN EDGE OF PRAIRIE
BURR OAK 18 S13W 181.50'; BURR OAK 12 S47E 277.20' NO OTHER NEAR LAND TIMBER & ?? SAME AS BEFORE

1858 PORTER TWP RD REC BK 1 PG 11 BEGINNING AT A POINT AT THE CENTER OF THE ROAD WHICH RUNS WESTERLY THROUGH THE NORTH HALF OF SEC 21 AND WHERE THE LINE THAT DIVIDES SEC 20 & 21 INTERSECTS SAID RD THENCE SOUTH ON THE SECTION LINE BETWEEN SEC 20 & 21 4521' TO A POINT 33' NORTH OF THE SOUTH WEST CORNER OF SEC 21; THENCE WEST 33'; THENCE SOUTH PARALLEL WITH THE SEC LINE BETWEEN SECTIONS 28 & 29, 5280' TO THE CENTER OF THE ROAD ON THE EAST & WEST QUARTER LINE OF SECTIONS 28 & 29 AND THIS LINE AS ABOVE DESCRIBED IS THE CENTER OF THE ROAD WHICH IS 66. WIDE. H. STEBBINS, SUPREVISOR OF PORTER

1864 LOCKE VOL 1 PG 213 FOUND BTS. VAR 7-50 2657.49 TO HH 19X14XB ABOVE 3 SMALL LIME STONE WITH 4 SMALL LIMESTONES ON N.S.E. & W, 5314.98 TO E 1/4 COR SEC 21

1977 BARNES VOL 5 PG 275 & FB#1 PG 55 DUG & FD NOTHING SET AT SINGLE PROPORTIONATE DISTANCE ON LINE WITH NE & SE CORNERS SEC 20. SET ALUM. MON. & REFERENCE SAME. 8' WEST OF EAST PVMT EDGE. ON LINE E/W FENCE LINE. 2666.72 TO NE & SE COR SEC 23

1985 LEE CSM VOL 13 PG 220 ALUM. MON. SOUTH TO 1" PIPE @ SE COR SEC 20

1992 KARNS #10036 ALUM. MON. S89-59-25E 1332.80 TO FD IRON, S00-04-50E 2665.96 TO FD IP @ SW COR SEC 21

1994 KARNS #9842 ALUM. MON. S89-59-25E 1332.80 FD IRON, S00-04-50E 2665.96 TO FD IP @ SW COR SEC 21

1999 HOULE ALUM. SOUTH 2666.42 TO PIPE @ SE COR SEC 20

2002 COMBS CSM VOL 25 PG 105 ALUM 2667.24 TO PK @ NW COR SEC 21

2003 COMBS CSM VOL 26 PG 221 ALUM N00-16-05W 2665.66 TO PK @ NE COR SEC 20

2007 GUARD #15724 FD ALUM. S00-00-04W 2666.46 TO 1" PIPE @ SE COR SEC 20 & S89-53-55W 2696.92 TO R/R SPIKE @ CENTER OF SEC 20. S89-53-55W 33.00 TO PIN ON R/W LINE.

FD ALUM. MON. 0.3' DEEP & REFERENCE PIPES

SHEET 1 OF 3

CORNER CODE P-9

Donald Barnes

Aug 18, 2009

PO576 E1/4CORSEC20

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.


Donald


Barnes
Embloss

Aug 18, 2009

SHEET 2 OF 3

CORNER CODE P-9

A.E. 7.08 REQUIREMENT

