

PO1538

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1886 RUBER VOL 2 PG 282 DROVE STAKE DEEP & PUT ON TOP OF IT LIMESTONE 15X8X3 & PUT HH STONE ON N & S SIDES OF LIMESTONE. 2692.47 VAR 6-30 TO W 1/4 COR, 2743.95 VAR 6-30 TO E 1/4 COR & VAR 5-7(?) 2628.78 TO N 1/4 COR SEC 11.

DUG & FOUND LIMESTONE 15"X8"X 3.5". DID NOT FIND STAKE OR HH STONES. REPLACED WITH POLY. MON. & PLACED CARBONITE POST NEXT TO POLY. POLY IS ON LINE WITH N/S FENCE LINE, NORTH OF PAVEMENT FOR STH 59, N20-45-05W 29.75' OF A 3/4X24 REROD WITH PLASTIC CAP. THE REROD IS 4' NORTH OF NORTH PVMT. EDGE AND 9' EAST OF N/S FENCE & UTILITY POLE LINE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Number of included sheets 1

Emboss
Donald Barnes
June 4 2001

CORNER CODE

A-E 7.08 REQUIREMENT

G-19

