

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:  
T. 4 N. R. 11 E. 4th P.M.  
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT  
REV 10/23/2004 USMONREC.DWG

**PORTER** TWP  
**ROCK COUNTY WI**

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6					5				4				3			2				1				B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North \_\_\_\_\_ Elev. \_\_\_\_\_  
 East \_\_\_\_\_  
 Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_  
 LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_  
 LONGITUDE \_\_\_\_\_  
 NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_  
 GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_  
 BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

**◆** CORNER MONUMENT      **○** WITNESS MONUMENT

BEARINGS ARE BASED ON:-----

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_ SHEET 1 OF 1  
 SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.  
 PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982  
 CORNER CODE W-9

1608 W1/16COR-NW1/4SEC33

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1875 RUGER VOL 2 PG 184 DROVE STAKE SURROUNDED BY 3 HH. VAR 6-27 1326.93 TO E 1/4 & NE CORNERS OF SEC 32. 1325.61 TO STAKE SURROUNDED BY 4 HH @ CENTER OF NE 1/4 SEC 32 & 2651.22 TO STAKE SURROUNDED BY 4 HH @ W 1/16TH COR OF NE 1/4 SEC 32.
- 1957 BATTERMAN VOL 3 PG 515 DUG 6X6X2 DEEP HOLE & FD NOTHING. DRAWING SHOWS @ RD INT.
- 1976 LEE CSM VOL 6 PG 49 FD PIN NO-01-10W 1328.63 TO NE COR SEC 32, S89-59-50W ALONG 1/16TH LINE.
- 1979 THOM CSM VOL 8 PG 320 SO-01-10E TO SE COR SEC 32
- 1982 BARNES VOL 6 PG 279 FD REROD NO-23-25W 1328.73 TO NW COR SEC 33 & S89-37-29E TO FD 1" PIPE.
- 1990 BARNES VOL 6 PG 279 FD PIN. NOO-23-25E 1328.73 TO NE COR SE 32.

FD 3/4" PIN 0.2' DEEP @ CENTER OF PVMT. I ALSO USED MY 1982 OBSERVATIONS @ THE FD PIN.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

THE FD PIN IS WITHIN 0.06' OF A LINE BETWEEN THE E 1/4 COR & NE COR OF SEC 32. IT IS ALSO 0.05' TO THE MIDPOINT. ACCEPTED FD PIN

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, DONALD BARNES, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

*Donald Barnes*  
Emboss

*Barnes*  
3-18-2009

SHEET 1 OF 1

CORNER CODE

**W-9**

A.E. 7.08 REQUIREMENT