

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 11 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

PORTER TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|----|---|---|---|---|---|----|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|
| A | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | A |
| B | | | | | | | | | | | | | | | | | | | | | | | | | | B |
| C | 6 | | | | | | 5 | | | | | | | | 3 | | | | | | | | | | | C |
| D | | | | | | | | | | | | | | | | | | | | | | | | | | D |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | E |
| F | | | | | | | | | | | | | | | | | | | | | | | | | | F |
| G | 7 | | | | | | 8 | | | | | | | | 10 | | | | | | | | | | | G |
| H | | | | | | | | | | | | | | | | | | | | | | | | | | H |
| J | | | | | | | | | | | | | | | | | | | | | | | | | | J |
| K | 18 | | | | | | 17 | | | | | | | | 15 | | | | | | | | | | | K |
| L | | | | | | | | | | | | | | | | | | | | | | | | | | L |
| M | | | | | | | | | | | | | | | | | | | | | | | | | | M |
| N | | | | | | | | | | | | | | | | | | | | | | | | | | N |
| O | | | | | | | | | | | | | | | | | | | | | | | | | | O |
| P | 19 | | | | | | 20 | | | | | | | | 22 | | | | | | | | | | | P |
| Q | | | | | | | | | | | | | | | | | | | | | | | | | | Q |
| R | | | | | | | | | | | | | | | | | | | | | | | | | | R |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | S |
| T | 30 | | | | | | 29 | | | | | | | | 27 | | | | | | | | | | | T |
| U | | | | | | | | | | | | | | | | | | | | | | | | | | U |
| V | | | | | | | | | | | | | | | | | | | | | | | | | | V |
| W | | | | | | | | | | | | | | | | | | | | | | | | | | W |
| X | 31 | | | | | | 32 | | | | | | | | 34 | | | | | | | | | | | X |
| Y | | | | | | | | | | | | | | | | | | | | | | | | | | Y |
| Z | | | | | | | | | | | | | | | | | | | | | | | | | | Z |

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: -----

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE P-7

PO4575 GEN20

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1977 BARNES VOL 5 PG 273 DUG & FOUND NOTHING**
- 1980 COMBS CSM VOL 10 PG 105 SET R/R SPIKE N89-45W
2665.11 TO FD ALUM @ W 1/4 COR SEC 20 & SO-10-40W
FROM CENTER TO S 1/4 COR.**
- 2003 COMBS CSM VOL 26 PG 209 FD R/R SO-10-40W 2675.14 TO
FD CI @ S 1/4 COR SEC 20 THENCE N89-43-56W 2656.72 TO
FD ALUM @ SW COR SEC 20**
- 2004 COMBS #15050 NO-10-14E FROM GEN SEC 20 TO N 1/4 COR
SEC 20**
- 2005 LATHROP CSM 28 PG 260 FD R/R NO-25-05W TO FD ALUM @
N 1/4 COR SEC 20 THENCE S89-33-44E 2705.28 TO FD PK @
NE COR SEC 20**
- 2007 GUARD #15724 N89-53-55E 2697.92 TO E 1/4 COR SEC 20,
SO-10-27E 2675.18 TO S 1/4 COR SEC 20, SOO-00-04W
2666.46 FROM E 1/4 COR SEC 20 TO SE COR SEC 20, & S89-
42-46W 2689.75 FROM SE COR SEC 20 TO S 1/4 COR SEC 20**
- 2007 COMBS CSM VOL 31 PG 97 FD R/R SPIKE. 2675.14 TO FD CI
@ S 1/4 COR SEC 20**

FD R/R SPIKE. THE SPIKE IS LESS THAN 0.06' OF THE COMPUTED INTERSECTION OF THE 1/4 LINES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?


ACCEPTED FD R/R SET BY COMBS @ CENTER OF SEC 20.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, DONALD BARNES, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

 Emboss
 Barnes

SHEET 1 OF 1

CORNER CODE P-7

11/13/2007 A.E. 7.08 REQUIREMENT