Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In: T. I.N. R. I.E. 4th P.M. CORNER CODE INDEX A B C C D B E F G H J K N N O P Q R S T U V W X Y Z 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 12 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24	ROCK COUNTY WI C
PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX	WITNESS MONUMENT

FIELD BOOK _____ PAGE # ____ OF Z_SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

BEARINGS ARE BASED ON:_

PO4574 CENTERSEC SEC 19

- (B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.
- 1868 LOCKE VOL 1 PG 329 [ESTABLISHED AT INT OF 1/4 LINES]
 SET STAKE WITH HH ON S,E,W IN WEST EDGE OF WATER
 HOLE. VAR 8-04 2525.49 TO W 1/4 COR SEC 19. VAR 8-05
 2676.30 TO N 1/4 COR SEC 19.
- 1899 BROWN VOL 2 PG 510 FD STAKE SURROUNDED BY 4 HH. 2661.12 TO E 1/4 COR SEC 19.
- 1957 BATTERMAN JR. VOL 3 PG 519 DUG 6X6X3 1/2 DEEP HOLE FD 1 1/2 WOODEN STAKE SURROUNDED BY 4 HH. SET 3/8 STEEL PIN IN STAKE AND 1 1/2 PIPE ABOVE PIN. REFERENCED SAME. SHOWS ON LINE WITH E/W FENCES & IN MIDDLE OF RD. ABOUT 30-40 SOUTH OF CONCRETE CULVERT. 2674.43 TO N 1/4 COR SEC 19 2671.85 TO S 1/4 COR SEC 19.
- 1979 BARNES VOL 5-562 FD 1 1/4X24 PIPE. REPLACED IT WITH ALUM. MON.
- 1985 BARNES VOL 6 PG 346 NO-12-35E 2674.61 TO N 1/4 COR SEC 19 & SO-04-39E 2671.88 TO S 1/4 COR SEC 19

FD ALUM. MON. O.1' BELOW PVMT. & 2.7' WEST OF CENTER OF PVMT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MON

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
- I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SHEET 1 OF 2

CORNER CODE

A.E. 7.08 REQUIREMENT

