Paper weight-110# (minimum)

BEARINGS ARE BASED ON:_

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In: T. \(\frac{\pmathcal{N}}{N} \), R. \(\frac{\pmathcal{L}}{\pmathcal{E}} \), 4th P.M. CORNER CODE INDEX A \(\frac{1}{2} \) 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 B \(\frac{1}{2} \) C \(\frac{1}{2} \) D	ROCK COUNTY WI C D IF AVAILABLE
F G A S O A A A A A A A A A A A A A A A A A	E ROCK COUNTY COORDINATES PERFERRED F G H North Elev K East N Hor. Datum Vert. Datum O P LATITUDE ELLIPS. HT
R S T U V W X Y	R S LONGITUDE T V NAD83(91)NETWORK ADJ. YR W X GPS (X) TRAVERSE (X)
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX CORNER MONUMENT (a)	

FIELD BOOK _____ PAGE # ____ OF ____ SHEET ___ OF ____ SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.
PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE _

E-21

PO531 SECOR-SEC2

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON (OCT 29TH) T4N R11E 4TH MER. NORTH

BET. 11 & 12

1980.0 TRAIL CRS N.W.

2640.0 SET A POST AND RAISED A MOUND OF EARTH & SOD FOR COR TO QUARTER SECTION

4834.0 TRAIL CRS N.W.

SET POST FOR COR TO SECS 1,2,11,12 5280.0 NEAR THE NORTHERN EDGE OF PRAIRIE SET POST & RAISED MOUND. LAND ROLLING 1ST RATE PRAIRIE GROWTH GRASS & WEEDS

1833 (OCT 30) HARRISON EAST ON RANDOM BET SECS 1 & 12 T4N $R11E4^{TH}MER.$

2640 TEMPY QUARTER SEC COR.

5332.8 INT. E BDY 39.6' N OF P LAND ROLLING 2ND RATE THINLY AND BADLY TIMBERED WITH SMALL RED & BURR D ? ? GRASS & WEEDS COR WEST BET SECS 1 & 12

QUARTER SEC COR. (BURR O 8 858E 91.08' 2666.4 BURR 0 10 N38E 105.6' BURR 0 8 BURR 0 10}MARKED

5332.8 INT SEC COR.

1833 (OCT 30TH) HARRISON TAN RIIE NORTH BETWEEN SECS 1 & 2

1298.88 WHITE DAK 12 IN DIAM

QUARTER SEC COR. (BURR DAK 10 S9W 9.9'; BURR 2640.00 DAK 12 N49E 29.70' {BURR DAK 10; BURR DAK 12}MARKED

2772.0 MARSH

4488.0 LEAVE SAME CRS NE

5255.58 INT. N. BDY 32.34' EAST OF POST (WHITE OAK 18 S25E 85.14'; BURR OAK 12 825W 58.08' LAND ROLLING 2ND RATE WITH RED, BURR, AND WHITE OAK? ? GRASS & WEEDS OCT 30TH 1833

- 1858 PORTER TWP RD REC BK 1 PG 13 BEGINNING AT THE QUARTER POST ON THE SECTION LINE BETWEEN SEC 1 & 2 T4RANGE 11 EAST, THENCE RUNNING SOUTH ON THE SEC LINE BETWEEN SECTIONS 1 AND 2, 11 & 12 TO THE QUARTER POST INTERSECTING THE ROAD RUNNING EAST AND WEST THROUGH THE MIDDLE OF SECTIONS 11 & 12. """ 66' WIDE THE LINE SURVEYED TO BE THE CENTER OF SAID ROAD.
- 1871 RUGER VOL 2 PG 63 FD OLD STAKE & HARDHEAD STONE AT COR. DROVE NEW STAKE DEEP IN PLACE OF OLD ONE AND PUT ON TOP OF IT HH 16X8X7 & SURROUNDED IT BY A LOT OF STONES. 1349.86 TO HH 15X7X6 @ N 1/16TH COR OF NW 1/4 OF SEC 12.
- 1871 RUGER VOL 2 PG 78 FD OLD STAKE & HH STONE AT CORNER. DRIVE STAKE DEEP & PUT ON IT HH STONE 16X8X7 SURROUNDED IT WITH HH & SANDSTONE, 1349.86 TO HH 15X7X6 @ N 1/16TH COR OF NW 1/4 SEC 12, 2699.73 TO N 1/4 COR SEC 12
- 1874 RUGER VOL 2 PG 128 FD HH STONE ON CORNER VAR 8-11' 1321.82 TO HH 18X9X7 @ W 1/16TH COR OF SW 1/4 SEC 1. 2643.63 TO W 1/4 COR SEC 1
- 1886 RUGER VOL 2 PG 282 FD COR AS SET BY SELF. (WESTERLY) VAR 6-34 1595.44 TO STAKE SURROUNDED BY 3 HH, VAR 6-34 2707.32 TO N 1/4 COR SEC 11, VAR 6-30 2578.84 TO E 1/4 COR SEC 11.

1945 WIDOT STH 59 #3902

SHEET 1 OF 3

CORNER CODE E-21

Dula Barres 6-09-09

PD531 SE COR-SEC2

- 1961 BATTERMAN VOL 4 PG 95 FD HH SURROUNDED BY 4 HH AT THE SW COR SEC 1. REFERENCED SAME. CENTER OF THE RD & ON LINE WITH E/W FENCE LINES. FD HH 18X9X7 & REFERENCED SAME @ W 1/16TH OF SW 1/4 SEC 1
- 1971 LEE CSM 2-67 STATES NOTHING ABOUT MON.
- 1977 BARNES VOL 5 PG 276 FD NAIL THAT AGREED WITH TIES. SET ALUM MON. & REFERENCED SAME.
- 1991 COMBS CSM 15 -1 STATES NOTHING ABOUT THE MON. NORTH 1329.05 TO R/R SPIKE @ THE 1/16TH COR, FROM 1/16TH COR N89-17-55W 1272.25 TO N 1/16TH COR OF SE 1/4 OF SEC 1.
- 2007 RIESOP CSM VOL 31 PG 10 FD ALUM. S01-21-42E 2580.77 TO CONC. NAIL SET FROM TIES @ E 1/4 COR SEC 11. FROM E 1/4 COR SEC 11 TO ALUM @ CENTER OF SEC 11 IT IS S88-23-32W 2746.22

FD ALUM MON. 0.2' DEEP @ CENTER OF PVMT & REF. MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location. \square

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Embass

SHEET 2 OF 3

CORNER CODE E-21

