

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 4 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

Porter TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																											A
B																											B
C																											C
D																											D
E																											E
F																											F
G																											G
H																											H
J																											J
K																											K
L																											L
M																											M
N																											N
O																											O
P																											P
Q																											Q
R																											R
S																											S
T																											T
U																											U
V																											V
W																											W
X																											X
Y																											Y
Z																											Z

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: -----

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE R-21

PO591

SECORSEC23

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON (OCT) T4N R11E 4<sup>TH</sup> MER. NORTH  
BET. 26 & 25

2640.0 QUARTER SEC COR SET A POST & RAISED MOUND

5280.0 SET COR TO SECS 23,24,25,26 MARKED POST & RAISED A MOUND OF EARTH & SOD. LAND ROLLING 1<sup>ST</sup> RATE PRAIRIE SOIL HEAVY & GOOD. GROWTH GRASS & WEEDS.

1833 (OCT 29) HARRISON EAST ON RANDOM BET SECS 24 & 25  
T4N R11E 4<sup>TH</sup> MER

2640 QUARTER SEC COR (TEMPORARY)

5329.5 INT E BDY IN E EDGE OF PRAIRIE 34.32' S OF POST LAND ROLLING 1<sup>ST</sup> RATE PRAIRIE COVERED WITH GRASS & WEEDS

COR. WEST BET SECS 24 & 25

2664.75 QUARTER SEC COR. {SET A POST & RAISED A MOUND OF EARTH & SODS.

5329.5 INT. SEC COR.

1833 HARRISON (OCT 29TH) T4N R11E 4<sup>TH</sup> MER. NORTH  
BET. 23 & 24

2640.0 QUARTER SEC COR.

SET A POST & RAISED A MOUND OF EARTH & SOD

2838.0 ROAD FROM THE MOUTH OF CATFISH TO DOUGHERTY'S FURNANCE SUGAR CREEK CRS E & W

4543.44 BURR OAK 18 IN DIAM AND LEVEL PRAIRIE

5280.0 SET COR TO SECS 13,14,23, 24 {BURR OAK 18 S25W 31.68' BURR OAK 10 S25E 34.32'; BURR OAK 20 N25W 141.90'; WHITE OAK 15 N69E 69.30' LAND THE 1<sup>ST</sup> 4,488' IS HANDSOME ROLLING PRAIRIE - SOIL 1<sup>ST</sup> RATE- REMAINDER ROLLING 2<sup>ND</sup> RATE WITH BURR & WHITE OAK TIMBER.

1833 HARRISON (NOV) T4N R11E 4<sup>TH</sup> MER. EAST  
BET. 23 & 26

660.0 LEFT TIMBER & ENTER PRAIRIE

2640.0 TEMPY 1/4 SEC COR

4224.0 TRAIL NORTH

5303.76 INT EAST BDY 7.92' SOUTH OF POST LAND ROLLING 1<sup>ST</sup> RATE PRAIRIE WITH GROWTH OF GRASS & WEEDS SOME WILD INDIGO

WEST COR. WEST BET SECS 23 & 26

2651.88 SET A POST AND RAISED A MOUND OF EARTH & SOD FOR COR TO QUARTER SEC

5303.76 SEC COR

1847 PORTER TWP RD REC BK 1 PG 1 BEGINNING AT THE 1/4 POST ON THE SEC LINE BETWEEN SECTIONS 23,, & 24 T4N R11E EAST; THENCE SOUTH ON THE SEC LINE TWO & HALF MILES TO THE SOUTH WEST COR OF SEC 36 OF TOWN AND RANGE. THE LENGTH OF SAID ROAD IS 2 1/2 MILES. COURSES GIVEN ACORDING TO THE TRUE MERIDIAN. VARIATION OF NEEDLE 7 3/4. WE DO HEREBY CERTIFY THAT THE ABOVE ROAD WAS LAID AND SURVEYED ACCORDING TO OUR ORDERS & DIRECTIONS. JUNE 28 1847

1961 BATTERMAN VOL 4 PG 94 FD HH WITH RED STONE ON SOUTH SIDE AT NE COR SEC 26. IN CENTER OF PVMT. NORTH 10.00 TO PK, EAST 10.00 TO PK

1967 BATTERMAN VOL 4 PG 335 FD HH WITH RED STONE ON SOUTH SIDE. REFERENCED COR.

*Donald P. ...*  
NOV 04/2009

PO591 SECORSEC23

19?? WPL #3592 & 3625 FD HH WITH STONE ON SOUTH SIDE.  
1970 WIDOT GTH M #13073  
1977 BARNES VOL 5 PG 250 FD 1" PIPE 0.3' DEEP REFERENCED  
SAME. PK SHORT TIES 3.00 TO NE & SE.  
1977 BARNES VOL 5 PG 255 WEST 2713.64 TO S 1/4 COR SEC  
23, N1-06-20E 2646.17 TO E 1/4 COR SEC 23.  
1977 BARNES VOL 5 PG 267 2664.75 TO N 1/4 COR SEC 25 &  
2652.89 TO W 1/4 COR SEC 25.  
1977 BARNES VOL 6 PG 398 S89-36-38W 2713.63 TO S 1/4 COR  
SEC 23, N0-43-01E 2646.18 TO E 1/4 COR SEC 23, ANGLE  
91-06-22 @ SE COR SEC 23 FROM S 1/4 COR TO E 1/4 COR  
OF SEC 23.  
2003 LATHROP #14651 FD ALUM. MON 2694.52 TO FD ALUM @ N  
1/4 COR SEC 25.  
2005 LATHROP CSM VOL 29 PG 135 ALUM 2652.86 TO ALUM @ W  
1/4 COR SEC 25

FD 1" PIPE. IN THE FALL OF 2009 THE PIPE WAS PAVED OVER.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?


**ACCEPTED PIPE.**


D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

**NONE**

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal  


Emboss  


SHEET 2 OF 3

CORNER CODE **R-21**

11/04/09 A.E. 7.08 REQUIREMENT

