Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In: T. N. R. E. 4th P.M. CORNER CODE INDEX A 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 B C D D E F G D D D D D D D D D D D D D D D D D D	TWP ROCK COUNTY WI IF AVAILABLE ROCK COUNTY COORDINATES PERFERRED F G H North Elev. K East M Hor. Datum Vert. Datum O P LATITUDE R S LONGITUDE T U V NAD83(91) NETWORK ADJ. YR W X GPS (X) TRAVERSE (X)
T Z 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX CORNER MONUMENT (a)	BASED ON THE FOLLOWING CONTROL:

BEARINGS ARE BASED ON:_____

FIELD BOOK _____ PAGE # _____ OF SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.
PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE

D-21

PD2522

- (B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.
- RUGER VOL 2 PG 128 DROVE STAKE DEEP & PUT ON TOP OF IT HH STONE 18X9X7 & SURROUNDE IT WITH 4 HH STONES. VAR 8-11 1321.82 TO W 1/4 COR & SW COR OF SEC 1
- BATTERMAN VOL 4 PG 95 FD HH 18X9X7 AT W 1/16 OF THE 1961 S.W. 1/4 OF SEC 1-4-11. REFERENCED CORNER.

ALL TREES, FENCE LINES, AND REF. MONUMENTS ARE GONE. FD 1 1/4" PIPE 0.3' DEEP @ CENTER OF PVMT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PIPE. IT IS IN HARMONY WITH THE CALL DISTANCES. S1-19-56E 1323.28' TO ALUM MON @ SW COR SEC 1 & N1-18-25W 1324.34 TO ALUM MON @ NW COR SEC 1. PIPE IS 0.29 EAST OF A LINE BETWEEN THE NW & SW CORNERS OF SEC 1.

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, DONALD BARNES, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

SHEET 1 OF 2

Emboss

CORNER CODE D-21

A.E. 7.08 REQUIREMENT

