

# PLAT AND RECORD

169

COUNTY BUILDING  
IN CITY OF БЕЛОИТ

Of a Survey on Section T R E. of the 4 P. M. in Township  
Rock County, Wisconsin, made the 19

I hereby certify that the following is a correct record of said survey as made by me.

County Surveyor.

Bench	Backsight	Inst.	Fore sight	Top	Inter sight	Heights	Remarks
			3.356	10.294			
2.844	13.138						
			1.336	11.802			Aug 28 - 1874
1.440	13.242						
			2.890	10.352			
5.995	16.347						
15.194			1.153				Leaning Elm 16 E. Bank, N. of Stone's Bridge.
					6.920	9.427	Surface of Water just N. of Stone's Bridge.
						10.352	
5.360	15.712						
			5.619	10.093			
4.502	14.595						
			3.572	11.023			
5.176	16.199						
			3.570	12.629			
4.295	16.924						
					5.380	11.544	Surface of Water One Mile below Indian Ford
			1.642	15.282			
2.884	18.166						
			3.781	14.385			
3.680	18.065						
					5.683	12.382	Surface of Water at dam below Indian Ford.
			2.339	15.726			on stone E. bank
			1.127	16.938			on stone W. bank.
					0.186	17.879	Average top surface of E. section of dam at Indian Ford.
					1.495	16.570	Top surface of chute of dam at Indian Ford.
					0.538	17.527	Average top surface of W. section of dam at Indian Ford.
7.545	24.483						
					7.530	16.953	Surface of Water above dam at Indian Ford.
			6.203	18.280			
3.812	22.092						Dam at Indian Ford. Stone abutment W. end 45 ft. long.
			4.039	18.053			dry rubble wall.
5.305	23.358						W. section of dam proper 207 ft. long.
			5.355	18.003			W. abutment of chute 10 ft. long.
5.674	23.677						Chute 27 ft. long.
			4.183	19.494			E. abutment of chute 2 1/2 ft. long.
3.881	23.375						
			4.000	19.375			E. Section of dam proper 50 ft. long.
							E. abutment of dam 31 ft.

12.942  
7.530  
4.812

Copied From P. 125 Vol. 2 Original County Surveyor's Record.