Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public	Land IN CO	Survey C	Corners E. 4 CODE INI	In: 4th P.M. DEX	WI	WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT REV 10/23/2004 USMONREC.DWG MILTON			
A 1 2 3 4 5						TWP			
R	5				A B	ROCK COUNTY WI			
c c	- P	>	S	7	C	IF AVAILABLE			
E					H E	ROCK COUNTY COORDINATES PERFERRED			
F G	8		0	1	F G				
н ,				[Н	North Elev			
K L	~	16	15	Bi	D K L	East			
M N					M	Hor. Datum Vert. Datum			
O P Q	79	7	3	\$	A O P Q	LATITUDE ELLIPS. HT.			
RS	9			6	RS	LONGITUDE			
T U V W	70)	70		7,0		NAD83(91)NETWORK ADJ. YR 2012			
X Y	13r	├	30		X	GPS (X) $\underline{\hspace{1cm}}$ TRAVERSE (X) $\underline{\hspace{1cm}}$			
Z 1 2 3 4 5 PLACE N	MONUMEN	9 10 11 12 1 VT SYMBOL BOVE INDE	AT P		\perp	BASED ON THE FOLLOWING CONTROL: Township Project			
(a)	• (CORNER	MONUN	MENT	0 '	WITNESS MONUMENT			

ROCK COUNTY PROJECTION				
BASED ON:				
BEARINGS ARE BASED ON:				

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING

PAGE #

PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

FIELD BOOK _

OR OBSERVATION SHEET

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE

SHEET

J-19(1)

MI550 3 4//

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed. FD CUT LIMESTONE 0.5' ABOVE GRADE. MONUMENT WILL PROBABLY BE DISTROYED BY STH 26 RELOCATION PROJECT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CUT LIMESTONE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SHEET 1 OF 2

CORNER CODE J-19

A.E. 7.08 REQUIREMENT

May 18,2012

