

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B																										B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

FULTON TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: \_\_\_\_\_

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE G 15(1)

FU4537

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1859 RUGER 1-122 DIAGRAM SHOWS CENTER AS THE INTERSECTION OF THE 1/4 LINES. E/W 1/4 LINE IS VAR 7-57 & N/S 1/4 LINE IS VAR 8-38. DOES NOT STATE WHAT HE PLACED. BR O 10 N6-35W 32.01'; BR OAK 13 S17-30W 52.8'
- 1900 BROWN 2-515 R.R. IRON 2684.09 TO E 1/4 COR SEC 10, NORTHERLY 2315.78 TO CENTER OF HWY. 13, NORTHERLY 1320 TO STAKE & IRON.
- 1980 SANDSNES 6-19 REPORTED THE FOLLOWING CHANGES:  
HARRISON 302,325.997 IS 302,326.292  
2,251,651.943 IS 2,251,651.953
- 1988 NORTHROP G-15 THE 1 1/4" SMOOTH ROUND SOLID IRON ROD SET AT THE CORNER DESCRIBED HEREON WAS RE-SET FROM PREVIOUS SURVEYS F RECORD IN THE COUNTY SURVEYORS' OFFICE LISTED AS FOLLOWS: 1. BROWN SURVEY IN 1900, VOL 2 PG 515 OF C.S. BOOKS SHOWS A RAILROAD RAIL; 2. NUMEROUS DEED DESCRIPTIONS AFTER THIS DATE COMMENCE AT THIS POINT; 3. BJ SUNNY SURVEY STILL SHOWS AND USES RAILROAD RAIL IN 1942 ON PLAT OF SURVEY OF DL 270 AND PART OF DL 272; 4. V3 PG 40 OF C.S. BOOKS, UPDATED SURVEY BY KERCH MAKES REFERENCE TO RAILROAD RAIL BY BROWN AND B.T. STUMP FROM A RUGER SURVEY; 5. BJ SUNNY SURVEY MADE IN 1939, VOL 3 PG 427 C.S. BOOKS; 6. 1975 CITY OF EDGERTON CONTROL SURVEY BY GEORGE A WEIR, LAND SURVEYOR, ROYAL OAKS ENGINEERING GIVING STATE PLANE COORDINATES TO THIS CORNER. REFERENCED CORNER.

I FOUND A 1 1/4" PIN THAT IS 0.6' NORTH OF E/W FENCE AND EASTERLY REFERENCE PIPE THAT WAS SET BY NORTHROP. PLACED CARSONITE POST ON NORTH SIDE OF FENCE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PIN. IT IS IN HARMONY WITH RECORD DISTANCES.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald  
Embress

Barnes  
1/405/07

SHEET 1 OF 1

CORNER CODE

G-15(2)

A.E. 7.08 REQUIREMENT