Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For	Public Land Survey Corners In:					•	WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
	7	r.En.	R	3 E.	4th P.M	[.	REV 10/23/2004 USMONREC.DWG
	CORNER CODE INDEX 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24						TURTIE TWP
A 1 2	3 4 5	6 7 8	9 10 11 12 1	3 14 15 16 1	7 18 19 20 2	21 22 23 24 2	, s _A
В	6	5	>	<u></u>	2		B ROCK COUNTY WI
C						Y	C IF AVAILABLE
E							E ROCK COUNTY COORDINATES PERFERRED
F G		9	9	10			F G
H							н North Elev
K L	9	1	70	15	A	A. (3)	K East
M N	7		Y				M Hor. Datum Vert. Datum
O P Q	0	20	1	27	13	7	O P LATITUDE ELLIPS. HT
R S	20				6	4	R S LONGITUDE
T U V		79	28	7	76	25	T U V NAD83(91) NETWORK ADJ. YR
w			0			6	W
x	3	75	2	73	13°	30	x GPS (X) TRAVERSE (X)
Y Z 1 2	3 4 5	6 7 8	9 10 11 12 1	13 14 15 16 1	7 18 19 20 2	21 22 23 24 2	z BASED ON THE FOLLOWING CONTROL:
			T SYMBOL BOVE INDE		KUPEK		
Charles and the	Property (Marie Paris Paris)	• (CORNER	MONU	MENT	\circ	WITNESS MONUMENT

(a) CORNER MONUMENT O WITNESS MONUMEN

BEARINGS ARE BASED ON: ... ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____ OR OBSERVATION SHEET ____ OF ____ SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

BE553 SECORSEC12 & TU541

- B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.
- 1835 BRINK SET POST CORNER SECTION 12 & 13 IN PRAIRIE IN MOUND PIT SOUTH OF POST 4.62.
- 1936 SUNNY VOL 3 PG 296 FOUND IRON ROD 12" LOW. SET 1 1/2" IRON PIPE MONUMENT CAPPED ON TOP & REFRENCED SAME.
- 1957 BATTERMAN VOL 3 PG 510 CALLS FOR A PIPE & 2645.7 TO W 1/4 COR SEC 18.
- 1960 BATTERMAN VOL 4 PG 56 STATES NOTHING ABOUT CORNER. REFERENCED CORNER.
- 1995 BARNES J-1 FD 1" PIPE IN MON BOX & 1960 VOL 4 PG 56 TIES.
- FD 1 1/4" PIPE IN MON BOX @ PVMT INTERSECTION OF N/S & WEST RD. BOX IS ABOUT .7' BELOW SURFACE.
- C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PIPE.

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

 NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SEAL

SHEET 1 OF 2

D, I

CORNER CODE J-1(/)

A.E. 7.08 REQUIREMENT

D. II Banes Sep 19,2012

