

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 12E 4th P.M.

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																								
C																									
D																									
E																									
F																									
G	7																								
H																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

TWP
ROCK COUNTY, WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North 225,114.54 Elev. _____

East 475,090.73

Hor. Datum COUNTY Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

ELLIPS. DATUM
NAD83(91) _____ COUNTY _____ LIST _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

 CORNER MONUMENT

WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE G-9

BE536

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 HARRISON NORTH BET. SECS 8 & 9
297 SUMMIT OF RIDGE HEAD OF DRAUGHT
2640 QUARTER SEC 8 COR ON SUMMIT OF RIDGE CRS E & W. SET POST & RAISED MOUND.
5280 SET COR TO SECS 4,5,8,9 ON NORTH DECLINE OF RIDGE DESCENDING TO MARSH. SET POST & RAISED A MOUND.
- 1864 LOCKE VOL 1 PG 208 FD OLD STAKE 26.4' S OF JAMES CLINEHEY'S WEST FENCE. WHITE OAK STAKE 2" NORTH OF OLD STAKE. VAR 6-05 2657.16 TO CENTER OF SEC 8 (CENTER SET AT EQUAL DISTANCE METHOD) & 5314.32 TO W 1/4 COR SEC 8.
- 1962 BATTERMAN VOL 4 PG 172 DUG & FOUND THE E 1/4 COR ON THE E/W CENTER LINE OF SEC 8. REFERENCED SAME.
- 1963 BATTERMAN VOL 4 PG 171 SET 1" PIPE IN MON. BOX & REFERENCED SAME.
- 1972 LEE VOL 4 PG 574 SET CI & REFERENCED SAME.
- 1977 LEE VOL 6 PG 198 2726.03 TO CENTER OF SEC 9.
- 1980 BARNES VOL 6 PG 108 FD MON. BOX 2670.52 TO CENTER SEC 8, 2644.02 TO NE COR SEC 8, & ANGLE 89-30-11 AT E 1/4 COR SEC 8 FROM CENTER SEC 8 TO NE COR SEC 8.

FOUND 1" PIPE IN MONUMENT BOX

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?
ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

Donald Barnes
seal
Oct 9, 1998

COUNTY SURVEYOR FILING DATA

Date of computer entry _____

Date microfilmed _____

Number of included sheets _____

CORNER CODE

EMBOSS LAND SURVEYOR SEAL

A-E 7.08 REQUIREMENT

G-9

Donald Barnes
029, 1998

**E 1/4 COR
SEC 8**

FED "CREEDY"
BRASS DISK IN
CONCRETE MON.
STA 101
SOUTH SIDE RD.
WEST OF DR. TO
AIRPORT NAV. SITE

1" PIPE
IN MON. BOX

S89-54-34E 4007.50

S88-40-58E 2859.44

FED "CENTRAL"
AZM. MARK
BRASS DISK IN
CONCRETE MON.
STA #305
SOUTH SIDE OF
RD

S0-33-34E 1280.38

N72-18-46E 4193.21

S50-40-58E 3479.79

N4-27-07E 2145.58

FED "CREEDY"
AZM. MARK
BRASS DISK IN
CONCRETE MON.
STA 316
EAST SIDE OF AIRPORT
NAV. SITE DR.

S82-04-31E 6751.60

FED "CENTRAL"
DISK IN
CONCRETE MON.
STA #112
EAST SIDE OF RD.

