

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 2E 4th P.M.

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																								
C																									
D																									
E																									
F																									
G	7																								
H		8																							
I			9																						
J				10																					
K					11																				
L						12																			
M	18																								
N		17																							
O			16																						
P				15																					
Q					14																				
R						13																			
S							12																		
T								11																	
U									10																
V										9															
W											8														
X												7													
Y													6												
Z														5											

TWP
ROCK COUNTY, WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North 233,228.61 Elev. _____

East 483,213.17

Hor. Datum COUNTY Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

ELLIPS. DATUM
NAD83(91) _____ COUNTY _____ LIST _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

◆ CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE A-15

BE508

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT EAST ON SOUTH SIDE SECTION 34
2640 SET QUARTER SECTION POST IN PRAIRIE AND MADE A MOUND
5280 SET POST CORNERS SECTION 34 & 35 IN PRAIRIE AND MADE A MOUND
LAND ROLLING FIRST RATE PRAIRIE.
- 1858 CHURCH VOL 1 PG 80 ON THE SOUTH LINE IN CENTER BETWEEN LETTER B (NW COR SEC 3) AND FIG 21 (NE COR SEC 3) ONE STAKE MARKED NO BEARING. WEST OF S 1/4 COR SEC 34 2647.26 TO NW & NE CORNERS OF SEC 3
- 1858 CHURCH VOL 1 PG 81 2688.18 TO NE & NW CORNERS SEC 3 & 2956.14 TO CENTER OF SEC 3. VAR 5 1/2
- 1874 RUGER VOL 2 PG 143 ESTABLISHED CORNER FROM SEC CORNERS. DROVE STAKE DEEP & PUT ON TOP OF IT L.S. 13X7X5. THE CORNER IS 9 INCHES WEST OF CORNER ESTABLISHED BY CHURCH. 45.38' WEST OF S 1/4 COR SEC 34. 2702.29 TO NW & NE CORNERS SEC 3 VAR 5-25. VAR 5-29 TO S 1/4 COR SEC 3. CORNER ON A STRAIGHT LINE BETWEEN THE NE & NW CORNERS OF SEC 3.
- 1965 BATTERMAN VOL 4 PG 169 FOUND PIN OVER LIMESTONE. SET MONUMENT BOX & REFERENCED SAME. 45.51 WEST OF S 1/4 COR SEC 34.
- 1965 DOT Z15 CITES MON BOX BY BATTERMAN. STA 26+24.90 & THE S 1/4 COR SEC 34 IS STA 26+58.
- 1990 BARNES Z15(1) FOUND 1" PIPE IN MONUMENT BOX. 45.52' WEST OF S 1/4 COR SEC 34 & REFERENCED SAME.

CORNER WAS NEVER ESTABLISHED BY THE ORIGINAL GOVERNMENT SURVEYOR. FOUND 1" PIPE IN MON BOX.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?
ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
NO

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

COUNTY SURVEYOR FILING DATA

seal

Donald Barnes
OCT 9, 1998

Date of computer entry _____

Date microfilmed _____

Number of included sheets _____

CORNER CODE

A-15

EMBOSS LAND SURVEYOR SEAL

A-E 7.08 REQUIREMENT

