

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:  
T. 1N., R. 12E 4th P.M.  
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

12 TWP

ROCK COUNTY, WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6					5																			
C																									
D																									
E																									
F																									
G																									
H																									
I																									
J																									
K																									
L																									
M																									
N																									
O																									
P																									
Q																									
R																									
S																									
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

North 222,620.01 Elev. \_\_\_\_\_

East 467,071.42

Hor. Datum COUNTY Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

ELLIPS. DATUM  
NAD83(91) \_\_\_\_\_ COUNTY \_\_\_\_\_ LIST \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

 CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE J-3

BE542

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 HARRISON WEST ON RAND. BET. 7 & 18
  - 2640 TEMPY 1/4 P
  - 2712.6 TRAIL CRS S.E.
  - 3630 LEAVE PRAIRIE & ENTER TIMBER
  - 5175.72 INT. WEST BOUNDARY AT NORTH EDGE MARSH
    - 61.38' SOUTH OF POST MARKED ? FOR 7 & 18. COR TREES TO SEC 7 & 18 {BURR OAK 10 N76E 81.18; BURR OAK 16 S86E 87.78
    - COR. EAST
  - 2535.72 QUARTER SEC COR. IN GROUND DESCENDING WESTWARD TO MARSH POST & RAISED MOUND
  - 5175.72 SEC COR
- 1878 RUGER VOL 2 PG 260 FOUND OLD COR. SET HH STONE 20X11X7.
- 1960 BATTERMAN VOL 4 PG 110 STATES NOTHING ABOUT MONUMENT BUT REFERENCES COR. N/S 203,632.41; E/W 2,237,096.93
- 1975 SPRAGUE MAP #222 N/S 203,632.41; E/W 2,2378,096.93 2500.23 TO SW COR SEC 7 & 2653.53 TO CENTER SEC 7.
- 1983 STH 213 PROJECT 5571-01-21 SHEET 4.7 FOUND IRON PIN N/S 203,632.98; E/W 2,237,087.36
- 1984 WIDOT PROJECT 5571-01-21 (REV 8-2-84) FD 1" PIN, SHEET 4.7 N/S 203,632.98; E/W 2,237,097.36.
- 1991 COMBS CSM V15 P 235 FOUND PIPE
- 1993 COMBS CSM V17 PG 110 FOUND PIPE
- 1993 COMBS CSM V17 PG 137 FOUND PIN 2500.45 TO NW COR SEC 18
- 1993 KREBS MAP #9816 FOUND BENT PIPE USED NAIL W/FLAGGING FOR CORNER 2653.5 TO CENTER SEC 7.
- 1993 COMBS MAP #9867 FOUND PIPE
- 1994 COMBS CSM V17 PG 411 FOUND PIPE

FOUND BENT PIPE

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?  
ACCEPTED FOUND LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.  
NO

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

COUNTY SURVEYOR FILING DATA

seal

*Donald Barnes*  
*OCT 9, 1998*

Date of computer entry \_\_\_\_\_

Date microfilmed \_\_\_\_\_

Number of included sheets \_\_\_\_\_

CORNER CODE

EMBOSS LAND SURVEYOR SEAL

A-E 7.08 REQUIREMENT

*J-3*

Donald Barnes  
Oct 19, 1998

