## Paper weigh \_\_\_\_ minimum) PUBLIC LAND SURVEY MONUMENT RECORD U.S.

For Public Land Survey Corners in: WI T. N., R. 12E 4th P.M.	ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
CORNER CODE INDEX	PR 1887 188
A1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 2021 22 23 24 25	ROCK COUNTY, WI
C	IF AVAILABLE
E	ROCK COUNTY COORDINATES PERFERRED
G 7 9 9 10 10 10 10 10 10 10 10 10 10 10 10 10	North 227, 921.83 Elev.
K AB AT AB AB AB	East 467, 078,60
M	Hor. Datum COUNTY Vert. Datum
N 0 20 21 22 23 24	LATITUDE ELLIPS. HT.
Q P	LONGITUTE
7 30 29 21 26 25	ELLIPS. DATUM
V	NAD83(91) COUNTY LIST
× 3 3 3 3 30 30	GPS (X) TRAVERSE (X) BASED ON THE FOLLOWING CONTROL:
PLACE MONUMENT SYMBOL AT PROPER	DAGED ON THE TOLEOWING CONTROL.
LOCATION ON ABOVE INDEX	
◆ CORNER MONUMENT (a)	WITNESS MONUMENT
	(
j Ž	
NO C	
BASED	
ARE	
Ž Ž	
BEARINGS	
_	
	011000 / 20 2
FIELD BOOKPAGE # OF SHEET OF SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING	
PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982	
	corner code $\varepsilon$ - 3

## BE522

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 HARRISON WEST BET SECS 6 & 7

2640 TEMPY 1/4 SEC COR

5161.2 INT WEST BOUNDARY 31.02' SOUTH OF POST MARKED SAME FOR COR TO SECS 6 & 7. LAND &? SAME

COR. EAST

2521.2 QUARTER SEC COR. SET POST & MOUND ON HIGH GROUND 5161.2 SEC COR.

1870 RUGER VOL 2 PG 45 FOUND OLD STAKE IN MOUND. SET HH STONE 20X16X8 SURROUNDED IT WITH SEVERAL LIMESTONES. 2455.70 VAR 4-05 TO SW COR SEC 6 & 2647.26 VAR 4-43 TO SE COR SEC 6.

1881 LEE VOL 2 PG 328 2454.87 TO SW COR SEC 6. FOUND COR SET BY RUGER. USED TO SUBDIVIDE SEC 6.

1963 BATTERMAN VOL 4 PG 174 DUG & FOUND LARGE HH. SET MON. BOX & REFERENCED SAME. WPL N/S 208,933.78 E/W 2,237,045.36

1981 BARNES VOL 6 PG 144 2487.73 WPL TO SW COR SEC 6, 2655.49 TO SE COR SEC 6, 5382.40 (WPL) TO N 1/4 COR SEC 6,& ANGLE 89-10-06 AT SE COR SEC 6 FROM S 1/4 COR SEC 6 TO E 1/4 COR SEC 6.

FD 1" PIPE IN MON. BOX

- C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location? ACCEPTED FOUND PERPETUATED LOCATION
- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, established, reestablished, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

Seal COUNTY SURVEYOR FILING DATA

Date of computer entry

Date microfilmed

Number of included sheets

CORNER CODE

EMBOSS LAND SURVEYOR SEAL

A-E 7.08 REQUIREMENT

