

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 12E 4th P.M.

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																								
C																									
D																									
E																									
F																									
G	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	
H																									
I																									
J																									
K	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1							
L																									
M																									
N																									
O	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36							
P																									
Q																									
R																									
S	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

TWP
ROCK COUNTY, WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North 227,715.52 Elev. _____

East 480,435.28

Hor. Datum COUNTY Vert. Datum _____


LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

ELLIPS. DATUM
NAD83(91) _____ COUNTY _____ LIST _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

 CORNER MONUMENT

WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE E-13

BE527

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 HARRISON NORTH BETWEEN SECTIONS 9 & 10
2640 LEAVE PRAIRIE & SET CORNER TO QUARTER SEC IN TIMBER
{RED OAK 12 N78W 30.36'; RED OAK 12 S62E 33.66'
2831.4 WHITE OAK 12 IN DIAM
3217.5 HICKORY 10 IN DIAM
3758.7 WHITE OAK 12 IN DIAM.
4224 LEAVE TIMBER & ENTER PRAIRIE
5280 SET POST FOR COR TO SECS 3,4,9,&10 RAISED MOUND OF SODS
ON GROUND DESCENDING NORTH TO CREEK
NORTH BETWEEN SECS 3 & 4
1980 LEAVE PRAIRIE & ENTER A SMALL ? OF BURR OAK TIMBER CRS
N.W.
2640 QUARTER SEC CORNER MARKED {BURR OAK 12 N21W 22.44'; BUR
OAK 14 S32W 42.24'
2715.9 BURR OAK 8 IN DIAM.
3102 BROOK 5.28' CRS S.E.
3300 LEAVE TIMBER & ENTER PRAIRIE
3630 ALONG EAST EDGE OF MARSH EXT. WEST
5527.5 INT. NORTH BOUNDARY 82.5' WEST OF POST NEAR EAST EDGE
OF MARSH. SET A POST & RAISED MOUND. MARCH 19TH
EAST ON RANDOM BETWEEN SEC 3 & 10
1848 LEAVE PRAIRIE & ENTER NORTH POINT OF TIMBER
2442 LEAVE TIMBER & ENTER PRAIRIE
2640 TEMPY 1/4 SEC COR
4059 BROOK 6.6' CRS S.E.
5286.6 INT. EAST BOUNDARY 7.9 SOUTH OF POST. THE BROOK
MENTIONED AT 4059 IS A FINE STREAM WITH A GRAVELLY
BOTTOM
COR. WEST BET SECS 3 & 10
2643.3 QUARTER SEC CORNER ON GROUND DESCENDING N.E. TO CREEK.
POST & RAISED MOUND.
3432 A RED OAK 14 IN DIAM.
5286.6 INT. SEC COR.
EAST ON RAND. BET. SEC. 4 & 9
2640 TEMPY COR
5273.4 INT. EAST BOUNDARY 10.56' SOUTH OF POST.
COR. WEST
2636.7 QUARTER SEC COR ON GROUND SLOPING EAST. SET POST &
RAISED MOUND
5273.4 SEC COR.
1851 McVEAN VOL 1 PG 1 2648.58 TO S 1/4 COR SEC 4 & 2653.2 TO E 1/4 COR
SEC 4.
1851 McVEAN VOL 1 PG 2 2761.02 TO N 1/4 COR SEC 10.
184? TOWNSHIP ROAD RECORDS. E/W ROAD IS 1003.2 NORTH OF SE COR SEC 4.
1972 LEE CSM V2 PG 233 FOUND CI
1974 BATTERMAN MAP #209 CI MONUMENT N0-02-50W 2653.43 TO E 1/4 COR SEC
4 & S1-38-20W 2661.71 TO E 1/4 COR SEC 9

FOUND CAST IRON MONUMENT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?
ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

E-13

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

COUNTY SURVEYOR FILING DATA

seal

Date of computer entry _____

Date microfilmed _____

Number of included sheets _____
CORNER CODE

Donald Barnes
EMBOSS LAND SURVEYOR SEAL
Oct 9, 1998

A-E 7.08 REQUIREMENT

E-13

*Donald Barnes
Oct 9, 1998*

