

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 11 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

PORTER TWP

ROCK COUNTY WI

IF AVAILABLE

ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4					3					2					1	B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE N-5

P0563 SE-COR-SEC18

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 HARRISON (NOV) T4N R11E 4TH MER. NORTH**
BET. 19 & 20
1307.46 BURR OAK 12 IN DIAM
2640.0 QUARTER SEC COR {BURR OAK 12 NSW 24.42';
BURR OAK 12; BURR OAK 10} MARKED
4418.04 BURR OAK 12 IN DIAM
5280.0 COR TO SECS 17,18,19,20 {BURR OAK 12 S34E
27.72'; BURR OAK 18 N30W 60.72'; BURR OAK
18 S62W 116.82'; BURR OAK 18 N22E 60.72'
LAND ROLLING 2ND RATE L?? MOSTLY RED &
BURR OAK ?? GRASS & WEEDS
- 1833 HARRISON (NOV 4RD) T4N R11E 4TH MER. EAST ON**
RANDOM BET. 17 & 20
297.0 LEAVE TIMBER & ENTER PRAIRIE
2640.0 TEMPY 1/4 SEC COR
5289.90 INT. E BDY 33.00' NORTH OF POST LAND
MOSTLY ROLLING 1ST RATE PRAIRIE-GROWTH
GRASS & WEEDS
WEST COR. WEST BET 17 & 20
2644.95 QUARTER SEC COR {SET POST & RAISED A
MOUND OF EARTH & SOD
5289.90 SEC COR
- 1833 NOV 5 HARRISON T4N R11E 4TH MER. WEST BET 18 & 19**
2640.00 QUARTER SEC. COR. {BURR OAK 20 S43W
55.44'; BURR OAK 18 NORTH 26E 33.66' {BURR
O 20; BURR O 18} MARKED
5187.60 INT. WEST BDY 66.00' NORTH OF POST. {BURR
OAK 18 S24E 42.9'; BURR OAK 10 N22E 91.74'
LAND @ ? SAME
- 1833 HARRISON (NOV) T4N R11E 4TH MER. NORTH**
BET. 17 & 18
1558.26 BURR OAK 12 IN DIAM.
2640.00 QUARTER SEC COR {BURR OAK 18
N31W 10.56'; BURR OAK 12 N60E 27.06' BURR
OAK 18; BURR OAK 12} MARKED
2739.0 ENTER PRAIRIE
2842.62 ROAD E & W
5280.0 SET COR TO SECS 7,8,17,18 SET POST AND
RAISED MOUND OF EARTH & SOD LAND 1ST 1/2
MILE SAME 2ND 1/2 ROLLING PRAIRIE 1ST RATE
GROWTH GRASS & WEEDS.
- 1860 STEBBINS PORTER TWP RD REC BK 2 PG 2 BEGINNING AT**
THE SOUTH EAST COR OF SEC 18 T4N R11E; THENCE WEST
ON THE SEC LINE BETWEEN SECTION 18 & 19, 5280' TO THE
1/4 POST ON THE SOUTH LINE OF SAID SECTION 18;
THENCE WEST ON THE SAID LINE 2477.64' TO THE SOUTH
WEST COR OF SEC 18 AND THE WHOLE LENGTH OF THE
ABOVE SURVEYED RD IS 5117.64' COURSES ACCORDING TO
THE TRUE MERIDIAN, VARIATION OF NEEDLE 8. H.
STEBBINS-SURVEYOR
- 1860 STEBBINS PORTER TWP RD REC BK 2 PG 2 & 3 BEGINNING**
AT THE SOUTH EAST COR OF SEC 18 T4N R11E; THENCE
WEST ON THE SEC LINE BETWEEN SECTION 18 & 19, 5280'
TO THE 1/4 POST ON THE SOUTH LINE OF SAID SECTION 18;
THENCE WEST ON THE SAID LINE 2477.64' TO THE SOUTH
WEST COR OF SEC 18; AND THE WHOLE LENGTH OF THE
ABOVE SURVEYED RD IS 5117.64' COURSES ACCORDING TO
THE TRUE MERIDIAN, VARIATION OF NEEDLE 8.
- 1899 BROWN VOL 2 PG 510 FD STAKE HH N&S 2673.99 TO E 1/4**
COR SEC 19.

Donald Barnes
6-09-69

PO563 SECORSEC18
 1940 SUNNY VOL 3 PG 466 CORNER OF SEC 17,18,19,20 DUG 6X6 HOLE 4' DEEP FD NOTHING. ON LINE WITH WESTERLY N/S FENCE TO THE NORTH & CENTER OF THE RD.
 1970 BATTERMAN VOL 4 PG 487 TIE TO THE NW & NE. NORTH OF CENTER OF GTH M & ON LINE CENTER LINE OF BERG RD.
 1970 WIDOT GTH M #13090 PROJ 5927-1-00 SHEET 4.8. STATED NOTHING ABOUT MON. "ESTABLISHED FROM REFERENCES". TIES SHOWN ON MAP IS THE SAME AS IN VOL 4 PG 487. PLANS SHOWS GTH M WAS RELOCATED TO THE SOUTH.
 1971 LEE VOL 4 PG 533 AT NE COR SEC 19 FD ORIGINAL TIES AS SHOWN IN VOL 4 PG 487. ADDED 2-5/8" PINS AS REF AS SHOWN. REFERENCED COR. MAP SHOWS WEST OF BERG RD
 1979 BARNES VOL 5 PG 562 FD 3/2X22 BOLT 2' DEEP WITH LARGE HH ON WEST SIDE. REPLACED BOLT WITH CI MON IN LINE WITH CENTER OF GTH M TO THE WEST. REFERENCED SAME. 11 WEST OF WEST EDGE OF PVMT. & SOUTH OF E/W FENCE LINE. ALSO CALLS FOR REFERENCING CSM SURVEY MON. ON EAST SIDE OF BERG RD.
 1985 BARNES VOL 6 PG 346 WEST 2670.94 TO N 1/4 COR SEC 29
 1986 BARNES VOL 6 PG 360 WEST 2670.94 TO N 1/4 COR SEC 29 & N00-39-47E 2661.97 TO E 1/4 COR SEC 18
 1992 KUPSGH #11556 FD ROCK COUNTY ALUM. MON 2670.83 TO N 1/4 COR SEC 19
 1994 KARNS CSM VOL 17 PG 215 FD ROCK COUNTY ALUM. MON
 2003 LATHROP GSM VOL 26 PG 224 FD CI. N1-15-24E 2629.09 TO ALUM @ E 1/4 COR SEC 18, N89-24-27W 2670.89 TO PK @ S 1/4 COR SEC 18

FD CI MON WEST OF N/S RD.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CI. MON. & REFERENCE MONUMENTS. IN HARMONY WITH RECORD DISTANCES


D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

 Duboss
 Barnes

SHEET 2 OF 3

CORNER CODE **N-5**

A.E. 7.08 REQUIREMENT

6-09-09

