ö

BASED

BEARINGS ARE

## PUBLIC LAND U.S. SURVEY MONUMENT RECORD

For Public Land Survey Corners in: WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT T. \_\_N., R. \_\_/\_E CORNER CODE INDEX NEWARK TWP 18 19 2021 22 23 24 25 ROCK COUNTY WI IF AVAILABLE D Ε ROCK COUNTY COORDINATES PERFERRED North Elev. Hor. Datum \_\_\_\_\_ Vert. Datum \_ LATITUDE \_\_\_ \_\_\_\_ ELLIPS. HT. LONGITUTE GPS (X) \_\_\_ TRAVERSE (X) \_\_\_ BASED ON THE FOLLOWING CONTROL: PLACE MONUMENT LOCATION ON ABOVE INDEX O WITNESS MONUMENT **CORNER MONUMENT** (a) FOUND TIES IN VOLA P6 168

SHEET \_\_\_\_ OF \_\_\_

FIELD BOOK\_ \_\_PAGE # \_ SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

## NE568

(B)Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence vou considered, and whether the monument was found or placed.

1834 MILLER

PG 22 EAST RANDOM BETWEEN SEC 15 & 22

1782 ENTER MARSH SOUTH

2244 LEAVE SAME

5315.64 INTERSECT SEC LINE 19.14' NORTH OF POST LAND 2ND RATE GENTLY ROLLING TIMBER OAK & HICKORY OAK & HAZEL (UNDER GROWTH)

WEST CORRECTED BETWEEN SECS 22 & 15

2657.82 SET 1/4 SEC POST. YELLOW OAK 12 S67E 58.08'; YELLOW OAK 18 N12W 63.36'

3175.26 HICKORY 18 IN DIA

5315.64 SEC CORNER

1871 COLLINS REMONUMENTATION NOTES

PG 167

EAST BETWEEN 15 & 22 VARIATION 3-15

2698.74 INTERSECT 1/4 LINE 18.48' NORTH OF CORNER SET 1/4 STONE BY STUMP OF WITNESS TREE CORRECTED VARIATION 3-40

CONTINUED EAST VARIATION 3-18

5404.08 SECTION CORNER

1963 BATTERMAN VOL 4 PG 168 FD 6X6 CUT STONE AT THE N 1/4 COR SEC 22. SET MON. BOX OVER STONE. REFERENCED SAME.

1976 BARNES VOL 5 PG 144 2695.12 TO SW COR SEC 15

1998 HOLE #8080 5300.15 TO N 1/4 COR SEC 15.

1998 HOLE #9989 ANGLE OF 92-25-10 @ SW COR SEC 15 FROM W 1/4 TO S 1/4 COR SEC 15.

## FD CUT L.S. IN MON. BOX. L.S. IS 1.15' BELOW PVMT, 4.2' NORTH OF CENTER OF PVMT. DRILLED HOLE IN CENTER OF HIGH PT OF L.S., & ON LINE WITH N/S FENCE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

## ACCEPTED FD PERPETUATED LOCATION.

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
- I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Baires Baires Number of included sheets 1

CORNER CODE N-15

A-E 7.08 REQUIREMENT