U.S.

PUBLIC LAND SURVEY MONUMENT RECORD

ROCK COUNTY WI IF AVAILABLE ROCK COUNTY COORDINATES PER North Elev. East Hor. Datum Vert. Datum	
North Elev. East Hor. Datum Vert. Datum	REPRED
North Elev Hor. Datum Vert. Datum	HEHHED
North Elev. East Hor. Datum Vert. Datum	
Hor. Datum Vert. Datum	
	m

LATITUDE	ELLIPS.
LONGITUTE	
17 1 4 1 4 1 4 1 9 1 4 1	(V)
GPS (X) TRAVERSE	
BASED ON THE FOLLOWING CO	NTROL:
PLACE MONUMENT SYMBOL TAT PROPER	

BEARINGS ARE BASED ON:

OBSERVATION SHEET	N92535			
		CHE	ET OF	
SHOW A PLAN VIEW DRAWING DEPICTION PHYSICAL FEATURES, INCLUDING THE E	NG THE CORNER M	ONUMENT AND SUF		_
PLANNING & ZONING COMMITTEE ADOPTED THE	ABOVE FORM ON 12/2			

NE515

(B)Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER

NORTH BETWEEN SEC 5 & 6

349.8 BUR OAK 15 IN DIAMETER 2014.32 HICKORY 12 IN DIAMETER

2640 SET 1/4 SEC POST WHITE OAK 14 IN S89W 12.54', WHITE OAK 14 IN N89E 22.44'

2067.12 BUR OAK 16

4950 ENTER PRAIRIE

5250.96 INTERSECTED N. BOUNDARY 30.36' W OF POST. SET POST COR OF SECS 5 & 6 WHITE OAK 18 IN S5E 696.96'; BUR OAK 22 S12W 284.46'

LAND 2ND RATE GENTLY ROLLING. TIMBER OAK & HICKORY. OAK TO HAZEL ?? MARCH 13 1834.

1871 COLLINS REMONUMENTATION NORTH BETWEEN 5 & 6 VARIATION 7-30
2662.44 INTERSECT 1/4 LINE 7.26' EAST OF CORNER. SET 1/4 STONE BY
STUMPS OF WITNESS TREES. CORRECTED VARIATION 7-20
CONTINUED NORTH VARIATION 7-30

5180.34 SECTION CORNER.

- 1878 RUGER VOL 2 PG 244 STONE MON. VAR 7-00 2516.91 TO NW COR SEC 5, VAR 3-57 2674.65 TO CENTER OF SEC 5.
- 1937 SUNNY VOL 3 PG 357 AT NW COR SEC 6 DUG 6X8X4 DEEP FD NO MON. FD 6X6 STONE MON. SET 1 1/2X8" CAPPED PIPE ON TOP & REFERENCED SAME. 2517.9 TO NE COR SEC 6.
- 1957 BATTERMAN VOL 3 PG 521 1 1/2 CAPPED PIPE & REFERENCED SAME. 2521.22 TO NE COR SEC 6. AT NE COR 6 STONE MON NOT FD.
- 1969 BATTERMAN VOL 4 PG 470 SET MON. BOX OVER E 1/4 COR & REFERENCED SAME.
- 1975 BICKEL #3130 2679.20 TO CENTER OF SEC 5 & 2664.64 TO SW COR SEC 5.

FD C.I. & REFERENCE TIES IN VOL 4 PG 470

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
- I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

لددة

sheet 1 of 1

egodine

7-03-01

CORNER CODE C-5