

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6			5					4				3							2				1
C																								
D																								
E																								
F																								
G	1																							
H																								
I																								
J																								
K																								
L	18																							
M																								
N																								
O																								
P																								
Q	19																							
R																								
S																								
T																								
U																								
V																								
W																								
X																								
Y																								
Z																								

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

*Fd TIES
VOL 4 PG 460*

OBSERVATION SHEET

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE E-5

NE523

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER PG 37 WEST ON RAND BET. 6 & 7

132 ENTER MARSH S.E.

2838 LEAVE SAME

5336.76 INTERSECT RANGE LINE 3.96' S POST. LAND EAST HALF MARSH, W. HALF TIMBERED WITH OAK & HICKORY HAS ON IT SOME MARSHY SPOTS

EAST CORRECTION BETWEEN SEC 6 & 7

2696.76 SET 1/4 SEC POST IN MARSH & THICKET OF SMALL ASPENS ASPENS 5 IN N45E 6.6', ASPEN 6 IN S45W 7.26' BEARINGS TO COR OF SECS 6 & 7 BUR OAK 6 N73E 31.68' & BUR OAK 8 S60E 33.66'

PG 38 NORTH BETWEEN SEC 5 & 6

349.8 BUR OAK 15 IN DIAMETER

2014.32 HICKORY 12 IN DIAMETER

2640 SET 1/4 SEC POST WHITE OAK 14 IN S89W 12.54', WHITE OAK 14 IN N89E 22.44'

4047.12 BUR OAK 16

4950 ENTER PRAIRIE

5250.96 INTERSECTED N. BOUNDARY 30.36' W OF POST. SET POST COR OF SECS 5 & 6 WHITE OAK 18 IN S5E 696.96'; BUR OAK 22 S12W 284.46' LAND 2ND RATE GENTLY ROLLING. TIMBER OAK & HICKORY. OAK & HAZEL UNDERGROWTH MARCH 13 1834.

PG 37 EAST RANDOM BETWEEN SECS 5 & 8

2046 ENTER MARSH

2508 LEAVE MARSH

2970 CREEK BOTTOM

3960 CREEK 5.28 SW

4884 LEAVE CREEK BOTTOM

5267.46 INTERSECTED SEC LINE 7.92' SOUTH POST

WEST CORRECTED BETWEEN SEC 5 & 8

2537.7 HICKORY 12 IN DIAMETER

2634.06 SET 1/4 SEC. POST HICKORY 10 S70W 54.78'; BUR OAK N82E 51.48'

3729.66 HICKORY 12 IN DIAMETER

5267.46 SEC COR.

PG 36 NORTH BETWEEN SECS 7 & 8

1125.3 BUR OAK 16 IN DIA

2139.72 YELLOW OAK 6 IN

2640 SET 1/4 SEC POST YELLOW OAK 14 IN N12E 9.9'; YELLOW OAK 10 IN S70W 64.68'

4123.68 BUR OAK 5 IN DIA

5280 SET POST COR SECS 5,6,7,8 BUR OAK 10 IN S15W 24.42'; BUR OAK 10 IN N74E 85.8'

1871 COLLINS REMONUMENTATION PG 210 NORTH BETWEEN 5 & 6 VARIATION 7-30

2662.44 INTERSECT 1/4 LINE 7.26' EAST OF CORNER. SET 1/4 STONE BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 7-20

CONTINUED NORTH VARIATION 7-30

5180.34 SECTION CORNER.

PG 207 EAST CORRECTION BETWEEN SEC 6 & 7 VAR 4-30

2712.60 SET 1/4 STONE IN MARSH IN PLACE OF PLAINLY MARKED STAKE

CONTINUED EAST SAME VARIATION

5390.88 SECTION CORNER

PG 195

NORTH BETWEEN 7 & 8 VARIATION 6-50

2652.54 SET 1/4 STONE BY STUMPS OF WITNESS TREES

CONTINUED NORTH

5316.96 INTERSECT SECTION LINE 18.48' EAST OF CORNER SET STONE FOR 5,6,7,8 BY WITNESS TREES. CORRECTED VARIATION 5-50

SHEET 1 OF 2

Donald James
6-29-01

E 5

2641.32 SET 1/4 STONE BY WITNESS TREES

CONTINUED EAST VARIATION 6

3986.4 CREEK

5336.76 INTERSECT SECTION LINE 3.96' SOUTH OF CORNER

CORRECTED VARIATION 6-05

1878 RUGER VOL 2 PG 244 STONE MON. VAR 5-45 2641.32 TO S 1/4 COR SEC 5.

1937 SUNNY VOL 3 PG 357 COR 5,6,7,&8 FD 6"X6" STONE MON. SET 1 1/2"X6" CAPPED PIPE ON TOP & REFERENCED SAME.

1969 BATTERMAN VOL 3 PG 357 SET MON BOX OVER STONE.

1970 BATTERMAN VOL 4 PG 460 STATE NOTHING BUT SET TIES.

1975 BICKEL #3130 2649.92 TO S 1/4 COR SEC 5 & 2664.64 TO W 1/4 COR SEC 5

1981 TOWNSEND #13198 2658.92 TO W 1/4 COR SEC 8, 2649.92 TO S 1/4 COR SEC 5.

FD C.I. MON. 0.15' BELOW PVMT SURFACE. 1.2' EAST OF CENTERLINE & 8' SOUTH OF E/W FENCE LINE ON EAST SIDE OF RD.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Donald Barnes

emboss

6-29-01

Sheet 2 of 2

CORNER CODE E-5

A-E 7.08 REQUIREMENT