

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 1E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6																							
C		5																						
D			4																					
E				3																				
F					2																			
G	1																							
H		8																						
I			9																					
J				10																				
K					11																			
L	18					17																		
M							16																	
N								15																
O									14															
P										13														
Q	19										20													
R												21												
S													22											
T														23										
U															24									
V																25								
W																	26							
X																		27						
Y																			28					
Z																				29				
																					30			
																						31		
																							32	
																								33
																								34
																								35
																								36

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE C9

NE516

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER

NORTH BETWEEN SEC 4 & 5

264 ENTER CREEK BOTTOM

1683 BROOK 6.6' S,W, BOTTOM MARSH

1980 LEAVE SAME (BOTTOM)

2640 SET 1/4 SEC POST. BUR OAK 14 IN S4E 54.78'; BUR OAK 12 IN N49W 58.08'

3630 BUR OAK 14

3630 ENTER PRAIRIE

3729 BROOK 3.3' S.E.

5267.46 INTERSECT NORTH BOUNDARY 36.96 EAST OF POST SET POST IN MOUND OF EARTH AND SOD COR OF SEC 4 & 5. LAND ROLLING 2ND RATE OAK & HICKORY TIMBER. MARCH 11, 1834

1871 COLLIN REMONUMENTATION PG 197

NORTH BETWEEN 4 & 5 VARIATION 6-30

2570.04 SET STONE FOR 1/4 COR BY STUMPS OF WITNESS TREES WITH VARIATION OF NEEDLE REVERSED.

CONTINUED NORTH VARIATION 7-30

5109.72 SET STONE FOR CORNER OF 4 & 5 36.96' EAST OF PLYMOUTH CORNER NOV 2 1871

1878 RUGER VOL 2 PG 244 FD STONE MON. VAR 7-05 2534.40 TO NE COR SEC 5, VAR 5-40 2633.4 TO SE COR SEC 5, VAR 3-57 TO W 1/4 COR SEC 5.

1959 BATTERMAN VOL 4 PG 30 FD STONE & PIPE REFERENCED PIPE. DIAGRAM SHOWS STONE LAYING ON SOUTH SIDE OF PIPE.

1959 BATTERMAN #3125 FD 1" PIPE & SPLIT L.S. AT W 1/4 COR SEC 4. ANGLE OF 91-36 @ W 1/4 COR SEC 4 FROM NW COR SEC 4 TO E 1/4 COR SEC 4.

1975 BICKEL #3130 FROM REFERENCES. 2573.55 TO SW COR SEC 4 & 5408.48 TO W 1/4 COR SEC 5.

1999 HOULE #7543 FD R/R SPIKE. 5408.41 TO W 1/4 COR SEC 5 & ANGLE OF 87-34-35 @ W 1/4 COR SEC 5 FROM W 1/4 COR SEC 4 TO SW COR SEC 5.

FOUND R/R 0.2' DEEP AND REFERENCE PIPES. USED TIES TO ESTABLISH CORNER. DID NOT ACCEPT R/R SPIKE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

RESTORED CORNER THROUGH ACCEPTANCE OF OBLITERATED EVIDENCE LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

SEE DIAGRAM. CORNER IS N16-33-15W 0.66' OF FOUND R/R SPIKE.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Number of included sheets 2

emboss

Donald Barnes
Dec 1 2000

CORNER CODE C-9

A-E 7.08 REQUIREMENT

