

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																								
C																									
D																									
E																									
F																									
G	7																								
H		8																							
I			9																						
J				10																					
K					11																				
L						12																			
M							13																		
N								14																	
O									15																
P										16															
Q											17														
R												18													
S													19												
T														20											
U															21										
V																22									
W																	23								
X																		24							
Y																			25						
Z																				26					

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FD TIES IN
VOL 5 P6308

OBSERVATION SHEET 331

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE 53

NE542

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER MARCH PG 35 WEST RANDOM BETWEEN SEC 7 & 18
3762 ENTER MARSH CR SOUTH
5341.38 INTERSECTED RANGE LINE 2.64' NORTH OF POST. LAND SAME TO
MARSH WHICH IS 3RD RATE
EAST MARKED BACK
2701.38 SET 1/4 SEC POST. BUR OAK 14 IN N81E 132'; BUR OAK 20 S82W 75.9'
3131.7 YELLOW OAK 12 IN DIAMETER
4385.7 BUR OAK 15 IN DIAMETER
5341.38 SEC. COR. MARCH 12, 1834
1871 COLLINS REMONUMENTATION EAST BETWEEN 7 & 18 VARIATION 4-45
2735.7 SET 1/4 STONE BY LINE TREE AND ROOTS OF WITNESS TREES.
CONTINUED EAST SAME VARIATION
5429.16 SECTION CORNER
1977 BARNES VOL 5 PG 308 0.5' DEEP FD 1" IRON PIPE, 28" DEEP FD CUT STONE. SET
20" ALUM ON TOP & REFERENCED SAME. SKETCH SHOWS COR WEST OF DIRT
DR & ON LINE WITH N/S FENCE.

FD ALUM. MON. & REFERENCES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Number of included sheets **1**

emboss
Donald Barnes
6-29-01

CORNER CODE **J-3**

A-E 7.08 REQUIREMENT