

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:  
T. 1N., R. 11E

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6						5								4										1
D																									
E																									
F																									
G	7						8								10										12
H																									
J																									
K																									
L	18						17								15										13
M																									
N																									
O																									
P	19						20								22										24
Q																									
R																									
S	30						29								27										25
T																									
U																									
V																									
W																									
X	31						32								34										36
Y																									
Z																									

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEETS 421 & 773

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE 4-1

NE554

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT

NORTH ON EAST SIDE SECTION 13

2640 SET QUARTER SECTION POST BUR OAK 18 S35W 104.28'; BUR OAK 6 N13W 40.92'

3201 ENTER MARSH

5280 SET POST CORNER SECTION 12 & 13 MADE A MOUND OF EARTH AND SOD. FIRST 1/2 LAND ROLLING SECOND RATE THICKLY TIMBERED WITH BLACK WHITE AND BUR OAK LAST 1/2 LEVEL WET MARSH.

1871 COLLIN'S REMONUMENTATION NOTES

PG 204 NORTH ON WEST LINE OF SEC 18 VARIATION 6-30

2658.48 INTERSECT 1/4 LINE 7.26' EAST OF CORNER. SET 1/4 STONE IN PLACE OF STONE SET BY RUGER AGREEING WITH STUMPS OF WITNESS TREES. CORRECTED VARIATION 6-20

CONTINUED NORTH VARIATION 5-45

5330.82 SET STONE IN MARSH FOR CORNER OF 7 & 18 IN PLACE OF STAKE AND STONES IN MOUND.

1974 LEE VOL 5 PG 21 FD CUT STONE

1977 BARNES VOL 5 PG 308 FD CUT STONE & REFERENCED SAME. 127' WEST OF N/S FENCE.

FD CUT L.S. & REFERENCE MONUMENTS. LS IS 1' ABOVE GRADE

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION

Donald Barnes

7-09-01

NE554

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

THERE IS A N/S JOG AT THE SW CORNER OF SEC 18, WHICH SHOULD CAUSE A JOG @ THE W ¼ COR. OF SEC 18. SINCE COLLIN ACCEPTED THE STUMPS OF THE WITNESS TREES, HE MUST OF ACCEPTED THE STANDARD CORNER THAT MULLETT SET AS THE W ¼ COR SEC 18.

DURING MARCH OF 1833, HARRISON SURVEYED AVON TWP SOUTH OF SUGAR RIVER & IN JANUARY OF 1834, HE SURVEYED AVON TWP NORTH OF SUGAR RIVER. HE ALSO HAD A SPECIAL CONTRACT TO SURVEY THE SOUTH LINE OF SEC 36 AVON TWP, WHICH HE DID IN 1834. IN THE 1834 SURVEY HE NOTES WHILE SURVEYING THE NORTH LINE OF SEC 36 HE "INT. THE EAST BOUNDARY IN MARSH 924' ". IS THE "924'" THE DISTANCE TO THE RANDOM STATE LINE? LATER THAT SPRING, MILLER SURVEYED NEWARK TWP. IN THE TOWNSHIPS TO THE NORTH, STANDARD AND CLOSING CORNERS ON THIS LINE ARE DOCUMENTED AND PERPETUATED. MILLER'S FIELD NOTES STATE HE SET POSTS & BEARING TREES WHERE HE CLOSED ON THE AVON/NEWARK TOWN LINE FROM THE STATE LINE TO THE NW CORNER OF SEC 19. SINCE COLLIN ACCEPTED BEARING TREE EVIDENCE AT THE ¼ CORNERS ALONG THE TOWN LINE FROM THE SW COR SEC 31 TO THE NW COR SEC 19, HE MUST OF CONSIDERED THE AVON AND NEWARK CORNERS TO BE COMMON. SINCE THE ORIGINAL GOV. SURVEYORS SET STANDARD AND CLOSING CORNERS ON THIS LINE, DID COLLIN USE THE BEARING TREES AT THE CLOSING CORNERS FOR NEWARK OR AVON TOWNSHIP? HIS MEASUREMENTS SUPPORTS THE NOTION THAT HE USED MULLETT'S CORNERS.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

3541

  
emboss

sheets 2 of 2

7-9-01

CORNER CODE **L-1**

A-E 7.08 REQUIREMENT