

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

### CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6																							
C		5																						
D			A																					
E				3																				
F					2																			
G	1																							
H		8																						
I			9																					
J				10																				
K					11																			
L	18					16																		
M		17					15																	
N								14																
O									13															
P	19																							
Q		20																						
R			21																					
S				22																				
T					23																			
U	30																							
V		29																						
W			28																					
X				27																				
Y					26																			
Z						25																		

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PERFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE N 19

NE570

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 16 EAST RANDOM BETWEEN SEC 14 & 23  
5263.5 INTERSECT SEC LINE 3.96' SOUTH OF POST LAND SAME  
WEST CORRECTED BETWEEN SECS 14 & 23  
174.9 WHITE OAK 15 IN DIA  
1339.14 BUR OAK 18  
2631.42 SET 1/4 SEC POST BUR OAK 20 IN S19W 35.64'  
BUR OAK 20 IN N53E 38.94'  
4026 YELLOW OAK 10  
5263.5 SEC CORNER
- 1871 COLLINS REMONUMENTATION NOTES  
PG 154 EAST BETWEEN 14 & 23 VARIATION 8  
2608.98 SET 1/4 STONE BY STUMP OF WITNESS TREE  
CONTINUED EAST VARIATION 7-30  
5217.3 SEC CORNER
- 1881 LEE VOL 2 PG 329 FD MON. VAR 5-33 2666.4 TO CENTER OF SEC 14  
1963 BATTERMAN VOL 5 PG 106 COPIED FROM BELOIT REC VOL 4 PG 142. FD CUT  
STONE REPLACED WITH 1" PIPE. SET MON. BOX. REFERENCED SAME.  
1996 COMBS #8347 2606.05 TO SW COR SEC 14  
1997 LEUENBERGER CSM 20 PG 202 ANGLE OF 88-37-00 @ SW COR SEC 14 FROM W 1/4  
TO S 1/4 COR SEC 14. 2606.12 TO S 1/4 COR SEC 14, 2664.28 TO W 1/4 COR SEC 14

FOUND MAG. NAIL 1.3' NORTH OF CENTER OF PVMT. ALSO FD MAG. NAIL 3.00 TO THE EAST & 3.00' TO THE SOUTH.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND MAG. NAIL

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Number of included sheets **1**

emboss  
*Donald Barnes*  
*Dec 20, 2000*

CORNER CODE **N-19**

A-E 7.08 REQUIREMENT

