

U.S. PUBLIC LAND SURVET MONUMENT RECOND

For Public Land Survey Corners in the T. / N., R. // E

CORNER CODE INDEX



LOCATION ON ABOVE INDEX



NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
STATE PLANE COORDINATES

North (Y) 195722,006 Eleve. (Z)

East (X) 2, 187, 156, 264 zone

Hor. Datum _____ Vert. Datum

(a.)

CORNER MONUMENT

O WITNESS MONUMENT

COORDINATES WERE SUPPLIED BY WPL. THE SURVEY WAS BY GPS AND CONNECTED TO THREE ROCK COUNTY GPS CONTROL MONUMENTS: BROADHEAD (305S), AVON (312S), AND NEWARK EAST (313S).

NAD83(91) WISCOSNIN STATE PLANE COORDINATES, SOUTH ZONE. US SURVEY FEET.

Don barnes 211/95

BEARINGS ARE BASED ON

FIELD BOOK ___ PAGE # ___

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. THE CORNER MONUMENT SHALL HAVE THE FOLLOWING CHARACTERISTICS: 1) HAVE AT LEAST TWO PREDETERMINED BREAK-OFF POINTS. 2) IF BROKEN, LEAVE A PERMANENTLY MAGNETIZED REMNANT AT THE ORIGINAL POINT: 3) MUST BE EXTENDABLE. 4) THE CAP IS INSCRIBED ROCK COUNTY SURVEY MONUMENT - PENALTY FOR DISTURBING MARKER. 9) OR AN EXISTING CUT LIMESTONE. AN IRON PIPE 1 PM 10" (MINIMUM) MAY BE USED IN AREAS WHERE GNOUND WATER IS WITHIN ONE FOOT OF THE SURFACE. IF THE CORNER IS OCCUPIED BY AN IMPROVEMENT (MANHOLE, BURIED CABLE, ETC.) ANY DURABLE, DISTINCT MONUMENT MAY BE USED. CORNERS SHALL BE REFERENCED WITH AT LEAST 4 DURABLE WITNESS MONUMENTS. WITNESS MONUMENTS SHALL BE MADE OF CONCRETE, NATURAL STONE, IRON OR OTHER EQUALLY DURABLE MATERIAL, EXCEPT WOOD. DESCRIBE THE CORNER AND THE WITNESS MONUMENTS.

CORNER CODE

(b.)	Describe any Other	any record material	l evidence, evidence yo	Monument Du Conside	evidence, ored, and i	occupat: whether t	onal evide: he monumen	ice, testimo L Vas found (nial evidenc or placed	e or
F .										1.
	*									
	William Control									
							V			
						e de la companya de				
								e Maria Perference La Caraca		
(c.)	Was the	corner res	tored throu	igh accept	ance of ()) an obli	iterated as	ridence: locat		
	found pe	rpetuated	location?			,	rtelated ev	indire incat	100 Or. (2	, •
										1
(d)	by distar above.	nce and dis Show the di the corner	rection. S istances be	how the detween the	corner as iscrepancy corner as tablished	on the p	lan view d	r as restored or reestab rawing under d or reestab t 4 of the w	lished (a),	
•										
						•				
						-				
(e.)	Was the method, evidence	corner rec including e or used	established the direct for proport	through ions and o	iost corne distances determini	r proport to other ng the co	tionate met public lai orner locat	hods? If so	o, show the ners used a	s
	ı,									
	as	ıdentifi	ed by th	ie corne	, nereby er code	/ certi	fy tha	t the cor	rner poin	ts
	rec reg ins	overed oulations	r restor	ed as e	expresse	d belo	sned, mo w and in	a rield numented, conforma t manual Interior	re-monus	mented the
	of 1	Land Man	agement.					THEEL TOI	, sureau	*
	ł				CODM	V curr	BVAR ==:	•		
	1.							ING DATA		
	·	SEA	L .				puter En	try		
	1		•	1		Receive				
	•			i		Microf	-			
					Treas	urer's	Receipt	No.		
							ncluded			 ,
								-	COPAIC	
					AFFIX	YOUR I	LAND SUR	VEYOR SEA	L. CODE	P/3