

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

### CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6																							
C		5																						
D			A																					
E				3																				
F					2																			
G						1																		
H	1						8																	
I		8						9																
J			9						10															
K				10						11														
L					11						12													
M	18											15												
N		18											16											
O			18											17										
P				18											18									
Q					18											19								
R						18											20							
S							18											21						
T								18											22					
U									18											23				
V										18											24			
W											18											24		
X												18											24	
Y													18											24
Z														18										24

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PERFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT       WITNESS MONUMENT

BEARINGS ARE BASED ON: \_\_\_\_\_

OBSERVATION SHEET 609

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE V 17

NE609

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER PG 20 EAST RANDOM BETWEEN SEC 27 & 34.

1007.82 BROOK 1.32' NE  
4356 CREEK 9.9' SE  
4468.2 SAME CREEK NE  
4554 SAME CREEK SE  
4752 LEAVE CREEK BOTTOM  
5273.4 SEC LINE 8.58' SOUTH OF POST

WEST CORRECTED BETWEEN SEC 27 & 34

1290.96 BUR OAK 12  
2622.18 BUR OAK 12  
2636.7 SET 1/4 SEC POST BUR OAK 18 N87E 42.9'; BUR OAK 15 S1W  
67.98'  
2818.86 BUR OAK 10 IN DIA  
5260.2 SEC COR.

PG 15 NORTH BETWEEN 26 & 27

330 LEAVE POINT. TIMBER FOR LOW GROUND  
2640 SET 1/4 SEC POST YELLOW 6 S4-30W 405.24'; BUR OAK 10 S2E 212.5'  
3234 LEAVE LOW GROUND  
3613.5 BUR OAK 18  
4276.8 BUR OAK 18  
\*5280 SET POST CORNER OF SE S 22,23,26,27 LAND SAME AS LAST NOTHING.  
\*BEARINGS BUR OAK 18 N71E 54.78'; YELLOW OAK 10 S33W 29.7'

EAST RANDOM BETWEEN 26 & 35

1320 ENTER LOW GROUND C. SOUTH  
2772 LEAVE SAME  
5266.8 INTERSECT SEC. LINE 9.9' SOUTH POST. LAND 2ND RATE LEVEL OAK  
TIMBER

PG 14 WEST CORRECTED BETWEEN SECS 26 & 35

356.4 BUR OAK 12 IN  
2633.4 SET 1/4 SEC POST BUR OAK 6 IN S89E 5.35', BUR OAK 10 N40E 176.88'  
3973.2 YELLOW OAK 5  
4900.5 YELLOW OAK 12  
5266.8 SEC COR

PG 47 NORTH BETWEEN SECS 34 & 35

132 LEAVE UP LAND FOR LOW ??  
2640 SET 1/4 SEC POST BUR OAK 15 IN S22E 91.08'; BUR OAK 6 N54 1/2W 33'  
4435.2 CREEK C S.E. 33' ??  
4686 LEAVE WET GROUND  
5280 SET POST COR SECS 26, 27, 34 YELLOW OAK 15 IN N76-30E 42.9';  
YELLOW OAK 18 S51W 52.8' LAND LOW AND WET WITH SCATTERING  
OAK

1863 LOCKE VOL 1 PG 176 SET STAKE & 3 LIMESTONES. FD WEST BEARING TREE &  
STUMP OF EAST. VAR 5-10 2657.16 TO S1/4 SEC 27 & VAR 5-10 5314.32' TO SW  
CORNER OF SEC 27, VAR 6-15 2614.92 TO E 1/4 COR SEC 34. E 1/4 SEC 34 ON LINE  
WITH NE & NW CORNERS SEC 34. N 1/4 COR SEC 34 ON LINE WITH NE & NW  
CORNERS SEC 34.

1871 COLLIN'S REMONUMENTATION NOTES

PG 151 NORTH BETWEEN 26 & 27 VARIATION 5-30

2636.7 SET 1/4 STONE BY STUMP OF WITNESS TREE.

CONTINUED NORTH VARIATION 7-15

5273.4 SET STONE FOR CORNER OF 22, 23, 26, 27 BY STUMP OF WITNESS TREE

PG 163 EAST BETWEEN 27 & 34 VARIATION 5-15

2645.94 SET 1/4 STONE IN PLACE OF STAKE AND STONES AGREEING WITH  
STUMPS OF WITNESS TREE.

*Pedd Barnes*

7-02-01

SHEET 1 OF 2 V-17

CONTINUED EAST VARIATION 4-30

3965.94 OFFSET 577.5' SOUTH AT RIGHT ANGLE

5292.54 OFFSET NORTH AT RIGHT ANGLE INTERSECTING SEC CORNER AT  
584.76'. CORRECTED VARIATION 4-20

PG 149 NORTH BETWEEN 34 & 35 VARIATION 4-39

2601.72 SET 1/4 STONE BY STUMP OF WITNESS TREE

CONTINUED NORTH VARIATION 5-36

4121.7 CREEK

5217.96 SET STONE FOR CORNER OF 26,27,34,35 BY STUMPS OF WITNESS TREES

PG 150 EAST BETWEEN 26 & 35 VARIATION 4-15

2641.32 SET 1/4 STONE BY STUMP OF WITNESS TREE

CONTINUED EAST VARIATION 5-30

5289.9 SECTION CORNER

1930 BATTERMAN VOL 3 PG 175 FD STONE (MARBLE) MON. 6X8. 58.9' TO NW COR  
BARN, 77.8' TO NE BECKMAN'S STORE, & 38.2' TO SE COR OF BLACKSMITH  
SHOP. REFERENCED SAME.

1964 BATTERMAN VOL 4 PG 1 2614.96 TO E 1/4 COR SEC 34 & 2638.45 TO N 1/4 COR SEC  
35.

1979 BARNES VOL 5 PG 537 2636.85 TO E 1/4 COR SEC 27, 2642.40 TO S 1/4 COR SEC 27,  
AN ANGLE OF 92-30-59 @ E 1/4 COR SEC 27 FROM SE TO W 1/4 COR SEC 27, & AN  
ANGLE OF 180-11-23 @ E 1/4 COR SEC 27 FROM NE TO SE CORNERS OF SEC 27  
AN ANGLE OF 87-43-19 @ SE COR SEC 27 FROM S 1/4 TO E 1/4 CORNERS OF SEC  
27

1980 LEUENBERGER #3225 1321.28 FROM N 1/4 COR SEC 34 TO N 1/16TH COR OF THE  
NE 1/4 SEC 34

FD 1" PIPE IN MON. BOX. 1.8' WEST N/S PVMT. & ON LINE WITH E/W CENTER PVMT..

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found  
perpetuated location?

ACCEPTED FD 1" PIPE IN MON. BOX & TIES AS RECORDED IN VOL 4 PG 1.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the  
location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy  
on the plan view drawing under (a), above. Show the distances between the corner as previously restored or  
reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments  
shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including  
the directions and distances to other public land survey corners used as evidence or used for proportioning the  
corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was  
determined by me under my direction and control and that this U.S. Public Land Survey Monument Record  
is correct and complete to the best of my knowledge and belief.

seal

Sheet 2 of 2

emboss  
Donald Barnes

CORNER CODE V-17

7-02-01

A-E 7.08 REQUIREMENT