

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																								
C		5																							
D			4																						
E				3																					
F					2																				
G						1																			
H							18																		
I								17																	
J									16																
K										15															
L											14														
M												13													
N													12												
O														11											
P															10										
Q																9									
R																	8								
S																		7							
T																			6						
U																				5					
V																					4				
W																						3			
X																							2		
Y																								1	
Z																									

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE 2-3

NE 622

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1832 LYON PG 1 EAST ALONG THE SOUTH SIDE OF SEC 31 VAR 6-50E
2640 LEAVE SCATTERING TIMBER AND ENTER A HIGH PRAIRIE
WHERE SET POST FOR 1/4 SECTION CORNER. BLACK OAK 14
WEST 988.02' NO OTHER TIMBER NEAR.
5280 LEAVE PRAIRIE AND SET POST FOR CORNER TO SECTIONS 31 &
32

BUR OAK 10 N56 1/2E 37.62'

BUR OAK 17 S62E 7.26'

1871 COLLINS REMONUMENTATION NOTES

PG 198 WEST ON SOUTH LINE OF 31 VARIATION 4-45

2641.3 SET 1/4 STONE IN PLACE OF POINT OF OLD STAKE AGREEING
WITH WITNESS TREE

CONTINUED WEST VARIATION 5

5284.62 SET STONE FOR CORNER OF SEC 31 IN PLACE OF STAKE SET
BY MCVEAN AGREEING WITH STUMP OF WITNESS TREE

1965 BATTERMAN VOL 4 PG 240 FD CUT STONE MON. REFERENCED SAME.
SKETCH SHOWS AT CENTER OF N/S PVMT & 7.5' NORTH E/W FENCE.

1966 SHIMEALL #3247 2651.2' TO SW COR SEC 31

1977 SCHROEDER #3245 2659.50' TO CENTER OF SEC 31 & ANGLE OF 89-58-51
@ CENTER OF SEC 31 FROM S 1/4 TO W 1/4 COR SEC 31.

1984 LEE CSM 12 PG 332 1329.19' NORTH TO 1/16TH COR

1987 LEUENBERGER #12367 2643.04' TO SE COR SEC 31

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

FD CUT LIMESTONE & REFERENCE TIES IN VOL 4 PG 240.
L.S. IS AT END OF RD & OFF PVMT. PLACED CARBONITE POST.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Donald Barnes

emboss

7-11-01

sheet 1 of 1

CORNER CODE Z-3

A-E 7.08 REQUIREMENT