

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6					5									4										1
D																									
E																									
F																									
G	7					8									10										12
H																									
I																									
J																									
K																									
L	18					17									15										13
M																									
N																									
O																									
P	19					20									22										24
Q																									
R																									
S																									
T	30					29									27										25
U																									
V																									
W																									
X	31					32									34										36
Y																									
Z																									

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_


LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

 CORNER MONUMENT

 WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

*Fd TIES OF RECORD*

*Observation sheet 2518846*

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE X-13

NE617

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 19 NORTH BETWEEN SECS 33 & 34  
2415.6 BUR OAK 12 IN DIA  
2640 SET 1/4 SEC POST BUR OAK 18 S67E 16.5'; BUR OAK 12 N58W  
132.66'  
2838 ENTER MARSHY GROUND  
3162.72 BROOK NE 1.32'  
5280 SET POST COR SEC 33, 34, 27, 28 IN MOUND OF EARTH AND SOD. MARCH  
9, 1834
- 1863 LOCKE VOL 1 PG 176 SET STAKE SURROUNDED WITH 3 STONES. BEARING  
TREES GONE. VAR 5-45 2663.76' TO NW & SW CORNERS OF SEC 34, 2646.6' TO  
CENTER OF SEC 34, & 5293.2' TO E 1/4 COR SEC 34. (COR. SET ON LINE &  
MIDWAY)
- 1865 LOCKE VOL 1 PG 227 SEE 34 VAR 4-45 2638.68' TO CENTER OF SEC 33 & VAR 5-  
45 2647.92' TO SE SEC 33, & VAR 4-45 5277.36' TO W 1/4 COR SEC 33.
- 1871 COLLINS PG 162 NORTH BETWEEN 33 & 34 VARIATION 5  
2655.84 INTERSECT 1/4 LINE 17.82' EAST OF CORNER SET 1/4 STONE  
IN PLACE OF STAKE AND STONE AGREEING WITH STUMPS OF  
WITNESS TREES. CORRECTED VARIATION 4-36.  
CONTINUED NORTH VARIATION 5  
5315.64 SET STONE FOR CORNER OF 27,28,33,& 34 IN OLD MOUND.
- 1965 BATTERMAN VOL 4 PG 233 FD CUT STONE MON. REF. SAME.  
REFERENCED VOL 4 PG 380.
- 1968 BATTERMAN VOL 4 PG 380 STATES NOTHING ABOUT COR. REFERENCES COR.
- 1981 BARNES VOL 6 PG 205 FD CARPENTER SPIKE. SET ALUM. MON. (AGREES WITH  
TIES OF RECORD.)
- 1997 HOULE CSM 20 PG 401 2630.77 TO CENTER OF SEC 33
- 1998 HOULE CSM 21 PG260 2649.28 TO CENTER OF SEC 34, 2655.06 TO SW COR SEC 34  
FD ALUM. MON.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Donald Barnes

emboss

7-02-01

Number of included sheets 0

CORNER CODE X-13

A-E 7.08 REQUIREMENT