

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6																							
C		5																						
D			A																					
E				3																				
F					2																			
G	1																							
H		8																						
I			9																					
J				10																				
K					11																			
L	18					16																		
M							15																	
N								14																
O									13															
P										20														
Q											21													
R												22												
S													23											
T														24										
U	19																							
V																								
W																								
X																								
Y																								
Z																								

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET 169 731

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE X-17

NE618

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 14 NORTH BETWEEN SECS 34 & 35
132 LEAVE UP LAND FOR LOW ??
2640 SET 1/4 SEC POST BUR OAK 15 IN S22E 91.08'; BUR OAK 6 N54 1/2W 33'
4435.2 CREEK C S.E. 33' RAPID ??
4686 LEAVE WET GROUND
5280 SET POST COR SECS 26, 27, 34 YELLOW OAK 15 IN N76-30E 42.9';
YELLOW OAK 18 S51W 52.8'. LAND LOW AND WET WITH SCATTERING
OAK SET POST
- 1863 LOCKE VOL 1 PG 176 SET STAKE PUT AROUND IT 3 HH - STAKE GONE. VAR 6-15
2614.92' TO NE & SE CORNERS OF SEC 34, 2646.6' TO CENTER OF SEC 34 & 5293.2'
TO W 1/4 COR SEC 34.
- 1869 LEE VOL 1 PG 339 FD OLD STAKE & NW BT. VAR 5-11 ALONG E/W 1/4 LINE OF
SEC 35. USED TO SUBDIVIDE SEC 35
- 1871 COLLIN'S REMONUMENTATION NOTES
PG 149 NORTH BETWEEN 34 & 35 VARIATION 4-39
2601.72 SET 1/4 STONE BY STUMP OF WITNESS TREE
CONTINUED NORTH VARIATION 5-36
4121.7 CREEK
5217.96 SET STONE FOR CORNER OF 26,27,34,35 BY STUMPS OF WITNESS TREES
- 1964 BATTERMAN VOL 4 PG 1 2614.96 TO SW COR SEC 35. CORRECTED & SET MON
BOX 9/18/68 OFF. LINE THRU "WEST 1/4 COR FD R/R SPIKES 2' EASTERLY & 2'
WESTERLY SET BY C. SHIMEALL WHEN HE FD STONE". LINE IN TIE
DISTANCES WITH NEW DISTANCE. 2638.45 TO CEN SEC 35 5283.9 TO E 1/4 COR
SEC 35.
- 1968 BATTERMAN VOL 4 PG 1 CORRECTED & SET MON BOX 9/18/68 OFF. LINE IN
"WEST 1/4 COR FD R/R SPIKES 2' EASTERLY & 2' WESTERLY SET BY C.
SHIMEALL WHEN HE FD STONE". LINE IN TIE DISTANCES WITH NEW
DISTANCES.
- 1974 THOM CSM 4 PG 265 1326.60 WEST TO 1/16TH COR
- 1979 BARNES VOL 5 PG 536 5315.97 TO E 1/4 COR SEC 35, ANGLE OF 90-26-49 @ W 1/4
COR SEC 35 FROM E 1/4 TO SW CORNERS OF SEC 35, ANGLE OF 89-22-41 @ SW
COR SEC 35 FROM W 1/4 TO S 1/4 CORNERS OF SEC 35. FD MON. BOX OVER
STONE. 2606.56' TO SW.
- 1979 BARNES VOL 5 PG 537 SHOWS RECORD DISTANCES

FD STONE IN MON. BOX & RECORD TIES IN VOL 4 PG 1

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND L.S. AS PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

sheet 1 of 1

emboss
Donald Barnes
7-02-01

CORNER CODE X-17

A-E 7.08 REQUIREMENT