

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

### CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C	6																								
D																									
E																									
F																									
G	1																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

*Fd 1999 TIES  
E-3*

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 / OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE A 3

NE502

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT WEST ON SOUTH SIDE SECTION 31 (T2N R11E)  
660 LEAVE PRAIRIE & ENTER WOODLAND  
2640 SET QUARTER SECTION POST BUR OAK 14 N31E 116.16'; BUR OAK 16 N42W 80.52'  
5280 INTERSECTED RANGE LINE 264' SOUTH OF TEMPORARY POST FOR CORNER TO TOWNSHIP 1 & 2 N RANGES 10 & 11E. BUR OAK 14 S34E 15.84', BUR OAK 12 N82W 33', BUR OAK 12 S46W, BUR OAK 14 N68E. LAND ROLLING FIRST RATE BLACK WHITE AND BUR OAK. SEPT 6TH, 1833.
- 1833 ORIG GOV. PLAT. 2640 TO NE & NW CORNERS OF SEC 6.
- 1868 LOCKE PLYMOUTH TWP REMONUMENTATION NOTES PG 73  
SEP 14 1868 VAR 6 EAST ON SOUTH LINE SEC 31.  
2657.82 INTERSECTED 1/4 LINE 13.53' NORTH OF COR. FOUND WEST BT AND STUMP OF EAST BT COR IN CENTER OF HIGHWAY AND IN LINE OF FENCE RUNNING SOUTH VAR CORRECTED 5-43.  
CONTINUED EAST FROM 1/4 COR WITH VAR 6.  
5320.92 INTERSECTED EAST BOUNDARY 22.11' NORTH OF COR. VAR CORRECTED 5-31 1/4 MONUMENT MARKED 31 ON ITS NORTH FACE.
- 1871 COLLINS REMONUMENTATION NOTES PG 209  
EAST ON NORTH LINE SEC 6 VARIATION 5-52  
5283.96 SET STONE FOR CORNER OF 5 & 6 BY STUMP OF WITNESS TREE. PLYMOUTH CORNER IS 30.36' WEST.  
BACK  
2641.98 SET 1/4 STONE 13.2' W(?) OF PLYMOUTH CORNER. NOV 4TH 1871
- 1937 SUNNY VOL 3 PG 357 FD 6X6 STONE MON. SET 30" CAPPED PIPE ON TOP. AT S 1/4 COR SEC 31 FD 6X6 STONE MON. SET 1 1/2" CAPPED PIPE ON TOP. 13' APART.
- 1957 BATTERMAN JR. VOL 3 PG 521 2645.46 TO SEARCH AREA @ NE COR SEC 6.  
1957 BATTERMAN VOL 3 PG 522 2645.46 TO NE COR SEC 6. FD CAPPED PIPE AT N 1/4 COR SEC 6 & S 1/4 COR SEC 31. REFERENCED SAME. 13.12 BETWEEN CORNERS. 2645.46 TO NW COR SEC 6.
- 1999 TALARCZYK Z-3 FD PIPES SET BY SUNNY IN 1937. REFERENCED SAME. PLYMOUTH COR IS 13.30 EAST OF NEWARK COR.

FD CAPPED PIPE @ CENTER OF PVMT. 13.11' WEST OF PLYMOUTH COR. FD REFERENCE PIPES THAT TALARCZYK FOUND

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Number of included sheets 1

emboss

Donald Barnes  
Jan 4 2001

CORNER CODE A-3

A-E 7.08 REQUIREMENT