

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:
T. 1 N., R. 11 E

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																								
C	6																							
D																								
E																								
F																								
G	1																							
H																								
I																								
J																								
K																								
L	18																							
M																								
N																								
O																								
P	19																							
Q																								
R																								
S																								
T	30																							
U																								
V																								
W																								
X	31																							
Y																								
Z																								

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

Ed TIES IN VOL 5
PG 203

OBSERVATION SHEET 507

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE A-13

NE507

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT

WEST ON SOUTH SIDE SECTION 33

2640 SET QUARTER SECTION POST IN PRAIRIE AND MOUND OF EARTH AND SODS

3102 INDIAN PATH CS S.E.

5280 SET POST CORNER SECTIONS 32 & 33 MADE A MOUND OF EARTH AND SODS LAND ROLLING SECOND RATE DRY PRAIRIE

WEST ON SOUTH SIDE SECTION 34

2640 SET QUARTER SECTION POST WHITE OAK 16 N29E 155.76' BUR OAK ; BUR OAK 12 N60 1/2W 167.64';

3960 ENTER PRAIRIE

5280 SET POST CORNER SECTIONS 33 & 34 MADE A MOUND OF STONES 3 FEET IN DIAMETER AT BASE & 3 FEET HIGH FIRST 3/4 THINLY TIMBERED WITH BLACK WHITE AND BUR OAK THICK UNDERGROWTH HAZEL, BRIERS GRAPE VINES & LAST 1/4 RICH DRY PRAIRIE.

1833 HARRISON

NORTH BETWEEN SECS 33 & 34 T2N R11E

1188 LEFT PRAIRIE & ENTER TIMBER

1683 WHITE OAK 26

2268.42 WHITE OAK 18

2640 QUARTER SEC COR. BLK O 24 N35E 48.18'; WHITE OAK 16 S21E 31.02

4066.26 BLK O 36

5181.66 BLK O 28

5280 COR TO SEC 27,28,33,34 WHITE OAK 24 S35E 114.18'; LYM? 24

N78E 86.46'; RED O 30 N46W 45.54'; W.O. 34 S31W 75.9'; LAND ? 1ST RATE TIMB. BLK & W.O. ASPIN HICKORY. ? & LITTLE OR NO UNDERGROWTH

1834 MILLER MARCH 10

NORTH BETWEEN SECS 3 & 4

2319.9 TRAIL CRS N.W.

2640 SET 1/4 SECS POST IN MOUND OF EARTH AND SOD

5283.3 INTERSECT'N. BOUNDARY. 33.66' EAST OF POST. SET POST IN MOUND OF STONE. COR OF SEC 3 & 4. LAND ROLLING 2ND RATE.

1868 LOCKE PLYMOUTH REMONUMENTATION AUG 21 1868

PG 16 WEST ON SOUTH LINE SEC 34 VAR 6

264 SET OFF 3.3' SOUTH

528 SET OFF 6.6' SOUTH

1122 SET OFF 132' SOUTH

1518 SET OFF 1.65' SOUTH

2673 INTERSECTED 1/4 LINE 14.52' SOUTH OF COR. FOUND BTS AND OLD STAKE. VAR CORRECTED 5-58

CONTINUED WEST FROM 1/4 COR WITH VAR 6-22

3762 ENTER PRAIRIE

5339.4 INTERSECTED WEST BOUNDARY 30.36' SOUTH OF COR. FOUND LARGE LIMESTONE SET FOR CORNER. COR IN CENTER HIGHWAYS RUNNING N.E.&W SET MONUMENT IN MOUND OF STONES COVERED WITH EARTH VAR CORRECTED 5-43 1/4 MONUMENT MARKED 34 ON NORTH FACE.

PG 17 NORTH BETWEEN SEC 33 & 34 VAR 7 AUG 21 1868

2655.18 INTERSECTED 1/4 LINE .66' EAST OF COR. FOUND STUMPS OF BTS AND STAKE UNDER STONE ON CORNER. THE DISTANCE & COURSE OF EACH BT GIVEN FOR THE OTHER RIGHT WHEN EXCHANGED. COR IN CENTER OF HIGHWAY & IN LINE OF E & W FENCE. VAR CORRECTED 7-01. CONTINUED NORTH FROM 1/4 COR WITH VAR 7

3118.5 BROOK 3.96' WIDE COURSE SW

5318.28 INTERSECTED NORTH BOUNDARY 3.3' E OF COR. VAR CORRECTED 7-04.

WEST ON SOUTH LINE SEC 33 VAR 6-20 SEPT 11 1868

1214.4 CENTER SLUICE BRIDGE 4.62' WIDE

*Donald Barnes
6-29-01*

PAGE 1 OF 2

A-13

HIGHWAY AND IN LINE WITH FENCE RUNNING NORTH. SURROUNDED
MONUMENT BY HEAP OF LIMESTONES. CONTINUED WEST WITH VAR
6-20

- 2705.34 CENTER OF SOUTH END OF BRIDGE
5340.39 INTERSECTED WEST BOUNDARY 12.87' SOUTH OF OCR. VAR.
CORRECTED 6-04' 1/4 MONUMENT MARKED 33 ON ITS NORTH FACE.
- 1871 COLLINS REMONUMENTATION
PG 172 NORTH BETWEEN 3 & 4 VARIATION 6-30
- 2682.9 SET 1/4 STONE IN LINE WITH FENCES EAST & WEST.
CONTINUED NORTH VARIATION 6-25
- 5134.8 SET STONE FOR CORNER OF 3 & 4 33.66' EAST OF PLYMOUTH CORNER.
PG 173 EAST ON NORTH LINE OF SEC 3. VARIATION 5-50
- 5280 SECTION CORNER
BACK TO
- 2640 SET 1/4 STONE 1.98' EAST OF PLYMOUTH CORNER. OCT 26, 1871
PG 212 EAST ON NORTH LINE OF 4 VARIATION 5-40
- 5334.12 SECTION CORNER
BACK TO
- 2667.06 SET 1/4 STONE 31.02' EAST OF PLYMOUTH 1/4 CORNER. NOV 6TH 1871
- 1871 RUGER VOL 2 PG 75 FD STONE MON. SE 33 TO S 1/4 COR SEC 33 2667.88' VAR 5-25
& SE COR SEC 33 TO E 1/4 COR SEC 33 2650.06' VAR 6-15.
- 1873 RUGER VOL 2 PG 117 STONE MON. AT NW COR SEC 3 & SE COR SEC 33.66' EAST
OF PLYMOUTH COR.
- 1882 RUGER VOL 2 PG 403 2632.74 TO N 1/4 COR SEC 3, 2488.86 TO W 1/4 COR SEC 3.
- 1882 HOLMES VOL 2 PG 349 CALLS FOR MON. 2487.21 TO W 1/4 COR SEC 3
- 1957 BATTERMAN VOL 3 PG 520 33.66 BETWEEN CORNERS. NEWARK IS EAST OF
PLYMOUTH. 2640.72 TO THE WEST & 2637.63 TO THE EAST.
- 1967 BATTERMAN VOL 4 PG 317 FD CUT L.S. AT SE COR SEC 33 & NE COR SEC 4.
33.45 BETWEEN CORNERS. REFERENCED SAME
- 1976 BARNES VOL 5 PG 203 33.46 BETWEEN CORNERS. REFERENCED SAME.
- 1978 BARNES VOL 5 PG 473 33.45 BETWEEN CORNERS. FROM SE COR SEC 33 N89-02-
54W 2640.64 TO N 1/4 COR SEC 4, N0-00-02W 2655.96 TO E 1/4 COR SEC 33, & 2670.88
TO S 1/4 COR SEC 33.
- 1978 BARNES VOL 5 PG 481 SE COR SEC 33 FD PK & 6" DEEP FOUND CUT L.S. SET 6"
ALUM. MON. AT NE COR SEC 4 FD PK & 18" DEEP FD CUT L.S. SET 18" ALUM.
MON.

FD ALUM. MON. 4 WEST OF EAST PVMT EDGE PROJECTED FROM SOUTH & @
CENTER OF E/W PAVEMENT CENTER LINE.

*C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found
perpetuated location?*

ACCEPTED FOUND CORNER AS PERPETUATED.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was
determined by me under my direction and control and that this U.S. Public Land Survey Monument Record
is correct and complete to the best of my knowledge and belief.

seal

emboss
Donald Barnes
6-29-01

SHEET 2 OF 2

CORNER CODE **A-13**

A-E 7.08 REQUIREMENT