

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 7 N., R. 11 E

CORNER CODE INDEX

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F	1																								
G																									
H																									
I																									
J																									
K	18																								
L																									
M																									
N																									
O																									
P	19																								
Q																									
R																									
S	30																								
T																									
U																									
V																									
W																									
X	31																								
Y																									
Z																									

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

 CORNER MONUMENT

 WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET ³²⁸ ~~425~~

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE A 9

NE5_505

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT

WEST ON SOUTH SIDE SECTION 33

2640 SET QUARTER SECTION POST IN PRAIRIE AND MOUND OF EARTH AND SODS

3102 INDIAN PATH CS S.E.

5280 SET POST CORNER SECTIONS 32 & 33 MADE A MOUND OF EARTH AND SODS LAND ROLLING SECOND RATE DRY PRAIRIE

WEST ON SOUTH SIDE SECTION 32 (2N R11E)

66 LEAVE PRAIRIE AND ENTER MARSH

330 STREAM 2.64' C SOUTH

759 LEAVE MARSH AND ENTER WOOD LAND

1188 ENTER PRAIRIE

2640 SET QUARTER SECTION POST IN PRAIRIE SECTION POST IN PRAIRIE AND MADE A MOUND

5280 SET POST CORNER SECTION 31 & 32 IN PRAIRIE AND MADE MOUND LAND MOST ROLLING DRY PRAIRIE FIRST RATE. BY OBSERVATION VAR FOUND 7-35

1833 HARRISON *NORTH BETWEEN SEC 32 & 33 (T2NR11E)*

1320 ROAD CRS N.W.

2640 QUARTER SEC COR IN PRAIRIE ON GROUND DESCENDING S.E. SET POST & RAISED MOUND.

5280 COR TO SECS 28,29,32,33 IN A RAVINE CRS S.E. SET A POST & RAISED MOUND. LAND HIGH ? 1ST RATE PRAIRIE.

1834 MILLER *NORTH BETWEEN SEC 4 & 5*

264 ENTER CREEK BOTTOM

1683 BROOK 6.6' S,W, BOTTOM MARSH

1980 LEAVE SAME (BOTTOM)

2640 SET 1/4 SEC POST. BUR OAK 14 IN S4E 54.78'; BUR OAK 12 IN N49W 58.08'

3630 BUR OA 14

3630 ENTER PRAIRIE

3729 BROOK 3.3' S.E.

5267.46 INTERSECT NORTH BOUNDARY 36.96 EAST OF POST SET POST IN MOUND OF EARTH AND SOD COR OF SEC 4 & 5. LAND ROLLING 2ND RATE OAK & HICKORY TIMBER. MARCH 11, 1834

1868 LOCKE PLYMOUTH TWP REMONUMENTATION SEP 11 1868

PG 70 WEST ON SOUTH LINE SEC 32 VAR 6-20

0 SET OFF 12.87' SOUTH

406.89 CENTER OF BRIDGE OVER CREEK 7.92'

2640 SET TEMPORARY 1/4 COR. COR. LOST

5321.91 INTERSECTED WEST BOUNDARY 60.39' SOUTH OF COR. FOUND OLD STAKE & WHERE B.T.S WERE DUG OUT. COR. IN CENTER OF HIGHWAY RUNNING SOUTH & ON SOUTH SIDE OF E & W HIGHWAY

2649.08 SET 1/4 COR 20.96' WEST AND 36.63' NORTH OF TEMPORARY 1/4 COR. VAR CORRECTED (WHOLE LINE) 5-49

PG 69 WEST ON SOUTH LINE SEC 33 VAR 6-20

1214.4 CENTER SLUICE BRIDGE 4.62' WIDE

1712.04 CENTER SLUICE BRIDGE 3.96' WIDE

Donald Starnes

7-03-01

NE505

2668.71 INTERSECTED 1/4 LINE AT COR. FOUND OLD STAKE IN CENTER OF HIGHWAY AND IN LINE WITH FENCE RUNNING NORTH. SURROUNDED MONUMENT BY HEAP OF LIMESTONE. CONTINUED WEST WITH VAR 6-20

2705.34 CENTER OF SOUTH END OF BRIDGE

5340.39 INTERSECTED WEST BOUNDARY 12.87' SOUTH OF COR. VAR CORRECTED 6-04. 1/4 MONUMENT MARKED 33 ON ITS NORTH FACE.

PG 68 SOUTH BETWEEN SECS 32 AND 33 VAR 7-15

SEPT 11, 1868

0 SET OFF 10.89' EAST

2661.12 INTERSECTED 1/4 LINE 10.89' EAST OF COR. FOUND MOUND AT JUNCTION OF FENCES ON WEST SIDE OF HIGHWAY AND IN LINE OF E & W FENCES. VAR CORRECTED 7-15 CONTINUED SOUTH FROM 1/4 COR WITH VAR 7-15

5320.59 INTERSECTED SOUTH BOUNDARY 3.96' EAST OF COR. FOUND LARGE LIMESTONE ON COR. UNDERNEATH INDICATIONS OF STAKE. COR IN CENTER OF E & W HIGHWAY AND NEARLY IN LINE OF FENCE ON WEST SIDE OF HIGHWAY RUNNING NORTH. VAR CORRECTED 7-10

1871 COLLIN REMONUMENTATION

PG 197 NORTH BETWEEN 4 & 5 VARIATION 6-30

2570.04 SET STONE FOR 1/4 COR BY STUMPS OF WITNESS TREES WITH VARIATION OF NEEDLE REVERSED.

CONTINUED NORTH VARIATION 7-30

5109.72 SET STONE FOR CORNER OF 4 & 5, 36.96' EAST OF PLYMOUTH CORNER NOV 2 1871

PG 211 EAST ON NORTH LINE OF 5 VARIATION 5-43

5386.92 SET STONE FOR CORNER OF 4 & 5, 36.96' EAST OF PLYMOUTH CORNER

BACK

2693.46 SET 1/4 STONE 5.94' EAST OF PLYMOUTH 1/4 COR.

PG 212 EAST ON NORTH LINE OF 4. VARIATION 5-40

5334.12 SEC COR.

BACK TO

2667.06 SET 1/4 STONE 31.02' EAST OF PLYMOUTH 1/4 COR. NOV 6, 1871

1871 RUGER VOL 2 PG 75 STONE MON. @ SW 33 2655.84 VAR 6-20 TO W 1/4 COR SEC 33, 2665.41 VAR 5-20 TO S 1/4 COR SEC 33

1875 RUGER VOL 2 PG 193 STONE MON @ SE COR SEC 32 VAR 6-20 TO E 1/4 COR SEC 32

1878 RUGER VOL 2 PG 244 FD STONE MON. VAR 4-30 2688.18 TO N 1/4 COR SEC 5. VAR 7-05 2534.4 TO E 1/4 COR SEC 5.

1957 BATTERMAN VOL 3 PG 521 STONE MON. NOT FD 2640.72 TO N 1/4 COR SEC 4, AT SE COR SEC 32 DUG 15X15X4 1/2 DEEP & FD NOTHING.

1967 BATTERMAN VOL 4 PG 312 FD CUT L.S. AT BOTH CORNERS. REFERENCED SAME. 36.93 BETWEEN CORNERS. PLYMOUTH IS WEST OF NEWARK.

1976 BARNES VOL 5 PG 172 FD FLAGGED CARPENTERS NAIL. 2.5' DEEP FD CUT STONE. SET BERNTSEN & REFERENCED SAME.

1978 BARNES VOL 5 PG 473 S88-47-39E 2667.29 TO N 1/4 COR SEC 4, N88-23-24W 36.79 TO PLYMOUTH CORNER, N0-04-39E 2661.98 FROM SE COR TO E 1/4 COR SEC 32 PLYMOUTH TWP, & 2673.85 FROM SE TO S 1/4 COR SEC 33 PLYMOUTH TWP.

Donald Barnes

7-03-01

NE505

1978 BARNES VOL 5 PG 430 2651' FROM ALUM. MON. NEAR SE COR SEC 32 TO SOUTH EDGE OF EXCAVATION @ E ¼ COR SEC 32.

FD ALUM. MON. @ EAST PVMT EDGE & 4.5' NORTH OF CENTER OF PVMT. FD TIES OF RECORD IN VOL 5 PG 172

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal
Donald Barnes
emboss

7-3-01

sheet 3 of 3

CORNER CODE **A-9**

A-E 7.08 REQUIREMENT