

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4N. R. 11E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A	
B																										B	
C	6						5					4					3								2	C	
D																											D
E																											E
F																											F
G	7						8					9					10								11	G	
H																											H
J																											J
K	18						17					16					15								14	K	
L																											L
M																											M
N																											N
O																											O
P	19						20					21					22								23	P	
Q																											Q
R																											R
S																											S
T	30						29					28					27								26	T	
U																											U
V																											V
W																											W
X	31						32					33					34								35	X	
Y																											Y
Z																											Z

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

PORTER TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

- CORNER MONUMENT
- WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

OBSERVATION # T299

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE 2-23

PO632 S 1/4 COR SEC 36

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 (SEP 15TH) MULLETT & BRINK WEST ON SOUTH SIDE SECTION 36 T4N R11E

2640 SET QUARTER SECTION POST BUR OAK 8 N55 1/2 E 80.52' BUR OAK 12 N78W 8.58'
5280 SET POST CORNER SECTIONS 35 & 36 BUR OAK 16 N42W 63.36' BUR OAK 16 N46E 67.98' LAND ROLLING AND STONY SECOND RATE TIMBER WHITE BLACK AND BUR OAK VAR 8-45' [DIAGRAM]

1833 ORIG GOV PLAT NW COR SEC 1 CENTER TWP IS 125.40' WEST OF SW COR SEC 36 PORTER TWP.

1864 LOCKE VOL 1 PG 216 & #677 N 1/4 COR SEC 1 CENTER TWP SET HARD HEAD 16X10X10 61.38' WEST OF S 1/4 COR SEC 36, 2732.07 FROM N 1/4 COR SEC 1 TO NE & NW CORNERS SEC 1, VAR 7-55 2586.04 TO CENTER OF SEC 1. @ S 1/4 COR SEC 36 FD BTS AND LARGE STAKE SET ON CORNER.

DUG & DID NOT FIND THE STONE OF RECORD AT THE N 1/4 COR OF SEC 1 CENTER TWP. I PLACED A POLY MONUMENT ABOUT 0.5' WEST OF THE N/S FENCE LINE & AND ON LINE WITH E/W FENCE LINE. THERE ARE MANY BURIED GAS PIPELINE BOUNDARY POSTS MARKING THE N/S BURIED GAS LINE. THE PIPE LINE BOUNDARY POSTS ARE ABOUT 6-8' EAST OF THE N/S FENCE LINE. THE PIPELINE GOES EAST NEAR THE SECTION LINE AND THE POSTS ARE ABOUT 2' SOUTH OF THE E/W FENCE LINE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

BECAUSE OF THE PIPE LINE POSTS, I DID NOT DIG FOR THE MONUMENT @ THE S 1/4 COR OF SEC 36. DUG & FOUND NOTHING AT THE N 1/4 COR SEC 1 OF T3N R11E. OCCUPATION IS IN HARMONY WITH THE CENTER OF SEC 1 AND RECORD DISTANCES. PLACED POLY MON. WITH 2 MAGNETS ON BOTTOM OF POLY. PLACED CARSONITE 2' S25E OF POLY. S33-01E 1.4 TO FENCE POST @ INTERSECTION. USED OBLITERATED EVIDENCE TO PLACE THE CORNER. ESTABLISHED THE S 1/4 COR SEC 36 PORTER TWP ON LINE WITH THE N 1/4 COR SEC 1 AND NE COR SEC 1 OF CENTER TWP @ LOCKE'S RECORD DISTANCE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal


Emboss
Barnes

Apr 13, 2010

SHEET 1 OF 2

CORNER CODE **Z-23**

A.E. 7.08 REQUIREMENT

