

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 11 E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																										A
B																										B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

PORTER TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT

○ WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E-23

PO532 S1/4CORSEC1

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 (OCT 30) HARRISON EAST ON RANDOM BET SECS 1 & 12 T4N R11E 4TH MER.

2640 TEMPY QUARTER SEC COR.

5332.8 INT. E BDY 39.6' N OF P LAND ROLLING 2ND RATE THINLY AND BADLY TIMBERED WITH SMALL RED & BURR O ?? GRASS & WEEDS

COR WEST BET SECS 1 & 12

2666.4 QUARTER SEC COR. {BURR O 8 S58E 91.08' BURR O 10 N38E 105.6' BURR O 8 BURR O 10} MARKED

5332.8 INT SEC COR.

1871 RUGER VOL 2 PG 63 FD OLD STAKE & SE BT & STUMP OF N.E. BT SET LIMESTONE 18X6X5. 1349.86 TO 15X7X6 SANDSTONE @ N 1/16TH NW 1/4 COR SEC 12, 2699.73 TO NW COR SEC 12.

1871 RUGER VOL 2 PG 78 STATES NOTHING ABOUT COR. 1349.86 TO 15X7X6 SANDSTONE @ N 1/16TH COR OF NW 1/4 OF SEC 12, 2699.73 TO NW COR SEC 12.

1874 RUGER VOL 2 PG 128 SEE SEC 12 PG 39 VAR 8-23' 1319.18 TO E 1/16TH COR OF SW 1/4 OF SEC 1, 2638.35 TO 23X9X9 HH @ CENTER OF SEC 1

1886 RUGER VOL 2 PG 284 STATES NOTHING ABOUT MON. ON SOUTH LINE OF SE 1/4 OF SEC 1 FROM S 1/4 COR SEC 1: VAR 5-45 634.42 TO SANDSTONE 11X7X2 1/2; 1268.85 TO HH 18X12X4 @ S 1/16TH COR OF SE 1/4 OF SEC 1, 2537.70 TO SE COR SEC 1

1965 BATTERMAN VOL 4 PG 223 FD LS 18X6X5 0.5 EAST OF N/S FENCE & ON E/W FENCE WPL 1270.20 TO HH SURROUNDED BY 4 HH 1' NORTH OF E/W FENCE @ N 1/16TH COR OF NE 1/4 SEC 12, 2540.40 TO NE COR SEC 12.

FD LS 6X10X16 LEANING ABOUT 0.5' EST OF PLUMP. MEDIUM SIZE CONC. TO THE SE & NW. PLACED GARSONITE POST.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED LS. IT IS IN HARMONY WITH RECORD DISTANCES.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald

Emboss

Barnes

6-09-09

SHEET 1 OF 2

CORNER CODE E-23

A.E. 7.08 REQUIREMENT

