

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 14 E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																											A
B																											B
C	6																										C
D																											D
E																											E
F																											F
G	7																										G
H																											H
J																											J
K	18																										K
L																											L
M																											M
N																											N
O																											O
P	19																										P
Q																											Q
R																											R
S																											S
T	30																										T
U																											U
V																											V
W																											W
X	31																										X
Y																											Y
Z																											Z
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

◆ CORNER MONUMENT ○ WITNESS MONUMENT

BEARINGS ARE BASED ON: (a) _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE T-13

FULTON TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL: _____

FU597^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1836 (AUG) BURNHAM NORTH BETWEEN SECTIONS 27 & 28
194.04 BUR OAK 12 IN DI
2640 SET 1/4 SEC POST BUR OAK 14 N9E 23.1' BUR OAK
10 S5EW 37.62'
NO STATIONS
5280 SET POST COR TO 21,22,27,28
BUR OAK 12 N79E 178.86' BUR OAK 12 N70W
304.26' FIRST RATE BUR OAK OPENINGS
- 1867 LOCKE VOL 1 PG 282 FD STOMPS OF BTS & OLD STAKE SET
STAKE AND SURROUNDED IT BY 5 HARDHEADS. VAR 8-07
2654.68 TO GEN SEC 27, 5309.37 TO E 1/4 COR SEC 27, VAR
6-40 2646.60 TO NW COR SEC 27
- 1965 THORP #1400 NO MON FOUND (SHOWS FENCE INT.)
1968 THORP #1399 NO MON FOUND (SHOWS FENCE INT.)
1974 LEE VOL 5 PG 20 SET CI 2642.68 TO NW COR SEC 27,
2641.68 TO SW COR SEC 27, 5316.0 TO E 1/4 COR SEC 27,
1327.75 TO S 1/16TH COR OF NW 1/4 OF SEC 27, ANGLE 88-
38-59 @ W 1/4 COR SEC 27 FROM NW COR SEC 27 TO S 1/16TH
COR OF NW 1/4 OF SEC 27, ANGLE 91-23-38 @ W 1/4 COR SEC
27 FROM S 1/16TH COR OF NW 1/4 OF SEC 27 TO SW COR SEC
27. FD NOTHING. SET COR ON LINE WITH NW COR & STONES
FD ON COX RD AT PRORATED DISTANCE. WEST OF
PENNYCOOK RD.
- 1975 NORTHROP CSM VOL 5 PG 18 FD C.I.
1985 NORTHROP #13744 & #7421 C.I. S0-28-36W 2638.80 TO SE
COR SEC 28, S89-34-52W 2628.94 TO GEN SEC 28, S89-34-
52W 5270.34 TO E 1/4 COR SEC 28.
- 1987 SCHROEDER #12843 CALLS FOR COR BUT STATES
NOTHING ABOUT MON. CALLS FOR COR BUT STATES
NOTHING ABOUT MON. ANGLE 91-34-XX @ NW COR SEC 27
FROM N 1/4 COR SEC 27 TO W 1/4 COR SEC 27. 914.85 FROM
CENTER OF COX RD
- 1989 SCHROEDER #208 CALLS FOR SEC COR BUT STATES
NOTHING ABOUT MON.
- 2000 NORTHROP #7634 CAST IRON MON OF RECORD BY C.S.
2638.80 TO SE COR SEC 28, 2628.94 TO CENTER SEC 28,
5270.34 TO W 1/4 COR SEC 28, ANGLE 91-07-25 @ SE COR
SEC 28 FROM S 1/4 COR TO E 1/4 COR SEC 28.
- 2002 NORTHROP #14234 C.I. 2628.94' TO GEN OF SEC 28

FD CI MON. AT FENCE INT. SET CARSONITE POST ON NORTH SIDE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CI

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

SHEET 1 OF 2

Emboss

Donald Barnes

1/9/07

CORNER CODE

T-13

A.E. 7.08 REQUIREMENT

