

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

FULTON TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3				2			1					B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: (a) _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE 29

FU625^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1835 (JAN 7) MULLETT & BRINK WEST SOUTH SIDE SECTION 32 T4N
R12E

66 LEAVE PRAIRIE
2344.32 B. OAK 12
2640 SET 1/4 SECTION POST B. OAK 12 N40E 31.68'
B. OAK 8 N77W 40.92'
5280 SET POST ON SECTIONS 31 & 32 W. OAK 20
N45E 53.46' BUR OAK 16 N28W 42.9' LAND
GENTLY ROLLING 2ND RATE
W? & BUR OAK

1835 (JAN) MULLETT & BRINK WEST SOUTH SIDE OF SECTION 33 T4N
12E

198' ENTER PRAIRIE
2640 SET 1/4 SECTION POST IN PRAIRIE B. OAK 12
S89 3/4W 1104.84' NO OTHER
5280 SET POST COR SECTIONS 32 & 33 IN PRAIRIE
BUR OAK 16 N89W 747.78' LAND GENTLY
ROLLING 1ST RATE PRAIRIE

1836 (MAR) D. LYON NORTH BETWEEN SECTIONS 4 & 5 T3N R12E
BEGAN AT POST CORNER TO SECTIONS 5, 8 & 9 ON
RIGHT BANK OF ROCK RIVER CRS E. SE

561 OVER RIVER SET POST ON LEFT CORNER TO
SECTIONS 4 & 5 {BUR OAK 14 N54E 32.34'
BUR OAK 16 N27W 73.92
990 LEFT RIVER BOTTOM
2640 SET QUARTER SECTION POST {BUR OAK 6
N45E 6.6' BUR OAK 7 N84W 29.04'
3209.58 B. OAK 14 INCHES IN DIAMETER
5082 ENTERED PRAIRIE
5321.58 INTERSECTED NORTH BOUNDARY 10.56' WEST
OF POST. SET POST COR TO SECS 4 & 5 {BUR
OAK 18 S70W 266.64' BUR OAK 15 S37E
540.54' LAND ROLLING & 2ND RATE TIMBER
BUR OAK

1836 (AUG) BURNHAM NORTH BETWEEN SECS 32 & 33
DRY RICH PRAIRIE

825 LEAVE PRAIRIE
2640 SET 1/4 SEC POST W. OAK 12 S28E 25.08' W.
OAK 14 N48W 45.54'
3302.64 Y. OAK 12 IN DIA
5280 SET POST COR TO 28, 29, 32, & 33 BUR OAK 16
N27 1/2E 29.04' BUR OAK 12 S52W 9.9' FIRST
RATE W. Y. & BUR OAK OPENINGS

1860 RUGER VOL 1 PG 142 @ NE COR SEC 5 CALLS FOR COR BUT
STATES NOTHING ABOUT MON. VAR 8-22 2691.48 FROM NE
COR TO E 1/4 COR SEC 5

1870 RUGER VOL 2 PG 27 FD REMAINS OF OLD STAKE & REMAINS
OF STUMP OF BEARING TREES. SET STAKE & SURROUNDED IT
WITH HARDHEAD STONES VAR 7-44 2640.33 TO S 1/4 COR SEC
33, 10.56' EAST OF NW COR SEC 4 JANESVILLE TWP, @ NW
COR SEC 4 FD BOTH BEARING TREES STANDING ALSO FD
REMAINS OF OLD STAKE. DROVE STAKE & SURROUNDED IT
WITH 5 SMALL HARDHEAD STONES.

1876 RUGER VOL 2 PG 207 SEE PAGE 20 & SEE PAGE 20 AT NW
COR SEC 4 & 2646.27 FROM NW COR TO N 1/4 COR SEC 4

1876 RUGER VOL 2 PG 209 FD COR EST BY SELF SEE PG 20, AT NE
COR SEC 5 FD COR. EST. BY SELF SEE PG 20. VAR 6-43
2691.98 FROM NE TO E 1/4 COR SEC 5 JANESVILLE TWP, SE
COR SEC 32 IS 10.56' EAST OF NE COR SEC 5, VAR 6-29
2644.78 FROM SE TO S 1/4 COR SEC 32, & VAR 6-29 2641.32
FROM NE TO N 1/4 COR SEC 5.

1971 SHIMEALL VOL 2 PG 27 AT SW COR SEC 33? OR NW COR SEC
4? SET PIPE & PLACED HHS AROUND IT.

SHEET 1 OF 2
CORNER CODE Z-9

Ronald Barnes
12/D4/07

FU625

- 1971 SHIMEALL VOL 2 PG 207 AT NW COR SEC 4 FD & SET I. PIPE
1975 BARNES VOL 5 PG 100 FD 4 HH 2' DEEP. FD WOOD FIBERS
AGREED WITH OCCUPATION & NW COR SEC 5. SET W-1-B
BERNTSEN MON. & REF. SAME. AT FENCE INT. 10.51 EAST OF
NE COR SEC 5. AT NE COR SEC 5 FD PIPE SURROUNDED BY 2
HH.
- 1976 NORTHROP #2221 FD 3/4 PIPE SURROUNDED BY STONES @ NW
COR SEC 4, WHICH IS 10.49 WEST OF ALUM. @ SW COR SEC
33.
- 1976 NORTHROP #6653 - LETTER NW COR SEC 4 JANESVILLE TWP
3/4" PIPE OVER 3 STONES BURIED ABOUT 18" BELOW
SURFACE.
- 1985 BARNES VOL 6 PG 344 SHOWS RECORD DISTANCES.
1986 BARNES C-9 2702.13 FROM NW COR SEC 4 TO W 1/4 COR SEC 4
JANESVILLE TWP
- 1987 BARNES A-9 FD ALUM. AT SE COR SEC 32 & PLACED WHITE
PLASTIC POST BY MON & REF. SAME. AT FENCE INT. 10.51
EAST OF NW COR SEC 4. AT NW COR SEC 4 FD PIPE
SURROUNDED BY 2 HH. SET WHITE PLASTIC POST NEXT TO
PIPE. 278,211.28; 2,243,784.37 FOR SE COR SEC 32 &
278,210.39; 2,243,773.90 ELEV 876.5 FOR NW COR SEC 4
- 1990 NORTHROP CSM VOL 14 PG 268 ALUM. 10.49' EAST OF 3/4
PIPE AT SE COR SEC 32. 2652.20 FROM NW COR SEC 4 TO N
1/4 COR SEC 4.

USED JANESVILLE TWP OBSERVATIONS. ACCEPTED ALUM. & REC.
REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED RECORD MONUMENTS.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Emboss


SHEET 2 OF 2

CORNER CODE **Z-9**

12/04/07 A.E. 7.08 REQUIREMENT