

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B																									B
C	6																								C
D																									D
E																									E
F																									F
G	7																								G
H																									H
J																									J
K																									K
L	18																								L
M																									M
N																									N
O																									O
P	19																								P
Q																									Q
R																									R
S																									S
T	30																								T
U																									U
V																									V
W																									W
X	31																								X
Y																									Y
Z																									Z

FULTON TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: (a) _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE X-9

FU616^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1836 (AUG) BURNHAM NORTH BETWEEN SECS 32 & 33
DRY RICH PRAIRIE
825 LEAVE PRAIRIE
2640 SET 1/4 SEC POST W. OAK 12 S28E 25.08' W.
OAK 14 N48W 45.54'
3302.64 Y. OAK 12 IN DIA
5280 SET POST COR TO 28,29,32, & 33 BUR OAK 16
N27 1/2E 29.04' BUR OAK 12 S52W 9.9' FIRST
RATE W. Y. & BUR OAK OPENINGS

1864 LOCKE VOL 1 PG 201 B. TREES STANDING VAR 7-5 2650.56
TO NE COR SEC 32, 2620.2 TO CEN SEC 32 & 5240.4 TO W 1/4
COR SEC 32

1865 LOCKE VOL 1 PG 243 & #6570 SEE PAGE 201, 2620.2 TO
CEN SEC 32 & 5240.4 TO W 1/4 COR SEC 32.

1870 RUGER VOL 2 PG 27 BOTH BEARING TREES STANDING, FD
REMAINS OF OLD STAKE. SET STAKE SURROUNDED IT WITH 4
HARD HEAD STONES VAR 7-46 2633.73 TO CEN SEC 33,
5270.76 TO E 1/4 COR SEC 33

1880 VOL 6 PG 333 1840-1888 TWP RD RECORDS IN COUNTY
CLERK'S VAULT. S84-30W 258.72' TO CENTER OF RD.

1964 SHIMEALL #1454 FD STAKE SURROUNDED BY HH STONES.
SET PIPE. ANGLE 89-51-30 @ E 1/4 COR SEC 32 FROM E/W
LINE OF SEC 32 TO NE COR SEC 32

1978 BARNES VOL 5 PG 396 FD 1 3/4X25" IP SURROUNDED BY 3
HH. SET ALUM. MON & REF SAME. AT FENCE INT.

1982 COMBS #13046 FD ALUM. MON

1985 BARNES VOL 6 PG 344 CALLS FOR REC. DISTANCE.

1988 SCHROEDER CSM VOL 13 PG 406

1993 COMBS CSM VOL 16 PG 207 FD ALUM 2662.91 TO NW COR
SEC 33.

1994 LATHROP #9590 STATES NOTHING ABOUT MON.

1995 COMBS CSM VOL 18 PG 284 FD ALUM 2662.91 TO NW COR
SEC 33.

2001 COMBS #7944 & 7945 ALUM. ANGLE 180-08-48 @ W 1/4 COR
SEC 32 FROM E 1/4 COR SEC 32 TO E/W 1/4 LINE SEC 31,
WESTERLY 1768.82 TO WEST R/W LINE OF NORTH RIVER RD.

2001 COMBS #7946 FD ALUM. 5272.76 TO W 1/4 COR SEC 32

FD ALUM. MON. & REFERENCE MONUMENTS. PLACED CARSONITE
POST.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found
perpetuated location?

ACCEPTED FD ALUM. MON.

D) Describe any material discrepancy between the location of the corner as restored or reestablished
and the location of that corner as previously restored or reestablished by distance and direction. Show
the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as
previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4
of the witness monuments shown on the drawing in (a), above.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index
was determined by me under my direction and control and that this U.S. Public Land Survey
Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald
Emboss

Barnes

12/03/07

SHEET 1 OF 1

CORNER CODE X-9

A.E. 7.08 REQUIREMENT