

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. ___ N. R. ___ E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

| | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | |
| A | | | | | | | | | | | | | | | | | | | | | | | | | A |
| B | | | | | | | | | | | | | | | | | | | | | | | | | B |
| C | | | | | | | | | | | | | | | | | | | | | | | | | C |
| D | | | | | | | | | | | | | | | | | | | | | | | | | D |
| E | | | | | | | | | | | | | | | | | | | | | | | | | E |
| F | | | | | | | | | | | | | | | | | | | | | | | | | F |
| G | | | | | | | | | | | | | | | | | | | | | | | | | G |
| H | | | | | | | | | | | | | | | | | | | | | | | | | H |
| J | | | | | | | | | | | | | | | | | | | | | | | | | J |
| K | | | | | | | | | | | | | | | | | | | | | | | | | K |
| L | | | | | | | | | | | | | | | | | | | | | | | | | L |
| M | | | | | | | | | | | | | | | | | | | | | | | | | M |
| N | | | | | | | | | | | | | | | | | | | | | | | | | N |
| O | | | | | | | | | | | | | | | | | | | | | | | | | O |
| P | | | | | | | | | | | | | | | | | | | | | | | | | P |
| Q | | | | | | | | | | | | | | | | | | | | | | | | | Q |
| R | | | | | | | | | | | | | | | | | | | | | | | | | R |
| S | | | | | | | | | | | | | | | | | | | | | | | | | S |
| T | | | | | | | | | | | | | | | | | | | | | | | | | T |
| U | | | | | | | | | | | | | | | | | | | | | | | | | U |
| V | | | | | | | | | | | | | | | | | | | | | | | | | V |
| W | | | | | | | | | | | | | | | | | | | | | | | | | W |
| X | | | | | | | | | | | | | | | | | | | | | | | | | X |
| Y | | | | | | | | | | | | | | | | | | | | | | | | | Y |
| Z | | | | | | | | | | | | | | | | | | | | | | | | | Z |

_____ TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

◆ CORNER MONUMENT

○ WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE L-9

FU556^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 (APR/MAR) HARRISON NORTH BETWEEN SECS 16 & 17 PG 21

1386 TRAIL N.E.

2640 QUARTER SEC. COR. {RED O. 10 S69E 16.5' RED O
12 N74W 68.64'

3851.76 WO 20 IN DIAM

4720.98 RED O 12 IN DIAM

5280 COR TO SECS 8,9,16,17 {BURR O 24 S30W 93.26'
RED OAK 12 N80E 64.02' BURR O 12 N24W 144.54'
& BURR O 10 S10E 81.84' LAND LEVEL 2ND RATE
TIMBER RED BURR & WHITE GRASS & WEEDS

1844 STEBBINS TWP RD REC BK1 PG 4 SURVEY OF A RD IN THE TOWN OF FULTON LEADING FROM THE NORTH LINE OF ROCK COUNTY TO THE INDIAN FORD ON ROCK RIVER MADE APRIL 19TH 1844. BEGINNING AT THE TERMINATION OF A RD LAID IN THE COUNTY OF DANE AT THE 1/4 POST ON THE SOUTH LINE OF SOUTH 32 T5N R12E, THENCE S 2 1/2E 5280' TO 1/4 POST SOUTH LINE OF S. 5 T4N R12E; THENCE SOUTH 1 EAST 3036' TO STAKE SET, POST OF BURR OAK, SOUTH 27W 6468', THENCE S32E 4966.5' TO A PT ON THE EAST LINE OF S 17, 662.64' NORTH OF THE 1/4 POST, THENCE S1/2E 3302.64' TO THE SE COR OF S 17 AND THE WHOLE LENGTH OF THE ROAD IS 16, 585.14'. COURSES

GIVEN ACCORDING TO THE TRUE MERIDIAN. VARIATION OF NEEDLE 7-30 HARRISON STEBBINS CO. SURVEYOR.

1845 STEBBINS TWP RD BK 1 PG 6 BEGINNING AT THE NORTH EAST COR OF SEC 17 T4N R12E ; THENCE SOUTH ON THE SECTION LINE 1977.36' TO A POINT ON SAID LINE 662.64' NORTH OF 1/4 POST. THE LENGTH OF SAID RD IS 1977.36'. COURSE GIVEN ACCORDING TO THE TRUE MERIDIAN. [GTH F]

1846 TWP RD BK 1 PG 8 SURVEY OF A RD TO DISCONTINUE A PART OF A RD IN THE TOWN OF FULTON. BEGINNING AT THE 1/4 ON THE LINE OF SEC 5 [S 1/4 COR] T4N R12E. THENCE S1E 3036' THENCE S32E 4966.5 TO A POINT ON THE EAST LINE OF SEC 17, 662.64' NORTH OF THE 1/4 POST [E 1/4 COR SEC 17]. THE WHOLE LENGTH OF RD TO DISCONTINUE IS 8002.5'

1875 RUGER VOL 2 PG 199 FD OLD STAKE & WHERE STUMPS OF BTS HAD BEEN DUG UP. SET LIME STONE 16X5X3 SURROUNDED IT BY 1 LIME & 3 HH STONES. VAR 6-31 2654.52 TO NW COR SEC 16, 2654.19 TO SW COR SEC 16.

1880 VOL 6 PG 333 THE FOLLOWING RD RECORD INFORMATION IS FROM A BOOK THAT IS IN THE COUNTY CLERK'S VAULT. THE RECORDS ARE FROM 1840-1888. SHOWS WEST LINE OF SW 1/4 OF SEC 16

1883 LEE VOL 2 PG 363 COR SET BY RUGER EAST 1953.6' TO DROVE POST IN CENTER OF NORTH EASTERLY RD. SOUTH VAR 6-25 698.28' TO STAKE SURROUNDED BY 4 HH

1932 DOT #11583 STATES NOTHING ABOUT MON. CALLS FOR CENTER OF STH 51 AS 1342' EAST & 868' NORTH OF W 1/4 COR SEC 16

1956 ELY "LADD PARK" BK 18 PG 28 STATES NOTHING ABOUT MON

1962 SANDSNES #7670 "STATE SCHOOL KRAFT SUB." 8" WOOD POST ON COR. 2660.00 TO SW COR SEC 16 & ANGLE 90-24 @ SW COR SEC 16 FROM W 1/4 COR SEC 16 TO S 1/4 COR SEC 16

1980 BARNES VOL 6 PG 42 DUG & FD NOTHING N89-29-30E 1955.3 TO INT. FENCE, S0-33-38W 2656.20 TO SW COR SEC 16, & N0-02-57W 2656.47 TO NW COR SEC 16.

SHEET 1 OF 3

CORNER CODE L-9

Donald
Barnes
11/07/07

FU556

- 1980 BARNES VOL 6 PG 44 DUG & FD NOTHING. AREA DISTURBED, SET ALUM. MON. AT SINGLE PROPORTIONATE MEASUREMENT USING RUGER'S DISTANCE FROM THE NORTHWEST TO THE SOUTHWEST COR. OF SEC 16. SET AT E/W DISTANCE THAT WOULD BE IN HARMONY WITH OCCUPATION IN THE NW 1/4 & SW 1/4 OF SEC 16 & REC DISTANCES. 2 SOUTH OF E/W FENCE & 5' EAST OF N/S FENCE.
- 1980 NORTHROP CSM VOL 10 PG 21 ALUM. MON. 2656.20 TO SW COR SEC 16
- 1982 BARNES VOL 6 PG 241 CONNECTED TO AERO-METRIC PHOTO CONTROL. 296,881.69; 2,243,802.84. FD ALUM. MON.
- 1988 NORTHROP CSM VOL 22 PG 83 ALUM. MON. 2656.20 TO SW COR SEC 16.
- 1995 LATHROP CSM VOL 18 PG 123 ALUM. MON. 2656.20 TO SW COR SEC 16
- 1999 LATHROP CSM VOL 22 PG 213 ALUM MON. 2656.20 TO SW COR SEC 16

USED 1980 FIELD OBSERVATIONS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED ALUM. MON.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Emboss

Barnes
11/07/07

SHEET 2 OF 3

CORNER CODE **L-9**

A.E. 7.08 REQUIREMENT

FULTON TWP
T4N R12E

ALUM
NE COR
SEC 17

E 1/4 COR
SEC 17 ALUM

SE COR
SEC 17

N00-01-30W 2656.45

S00-34-52W 2656.19

N 1/4 COR
SEC 17
ALUM

N89-17-22E 2668.44

N45-29-54W 3742.69

N89-22-09E 5331.10

N44-46-42E 3778.42

S63-54-31E 5905.67

ALUM

ALUM
W 1/4 COR
SEC 17

SHEET 3 OF 3

Donald Kaus
EMBOSSED SEAL
11-07/07

