Paper weight-110# (minimum)

Black nonfading ink required

## U.S. PUBLIC LAND SURVEY MONUMENT RECORD

	CODE INDEX	ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT REV 10/23/2004 USMONREC.DWG
	12 13 14 15 16 17 18 19 20 21 22 23 24 25 <sub>A</sub>	<u>Center</u> TWP
6 5 8		ROCK COUNTY WI
	D E F	IF AVAILABLE ROCK COUNTY COORDINATES PERFERRED
1 9	<del>-                                      </del>	NorthElev.
8 1		East
	MN	Hor. Datum Vert. Datum
0 0 0	Y AN AN OP OR	LATITUDE ELLIPS. H
30 79 79	b n no no s	LONGITUDE
7	U	NA DOC(04) NEWSYODIZ ADI NO
3 3	ک میں میں میں اور	GPS (X) TRAVERSE (X)
1 2 3 4 5 6 7 8 9 10 11	12 13 14 15 16 17 18 19 20 21 22 23 24 25	
PLACE MONUMENT SYM LOCATION ON ABOVE II	BOL AT PROPER NDEX  ER MONUMENT	MANAGO BAONINATAN
BASED ON: ROCK COUNTY PROJECTION SEGRETAS SEG 21 53" W alm  1 Live of the Swilf of Setting		FOUND CAST IRON MONUMENT TO SEE 3/8" X18"  SEE 3/8" X18"  FOUND CAST IRON MONUMENT TO SEE 3/8" X18"  S
ings are samed South 10-3-1	Set 3/8"x18" G Iron Pin Utility Box	80.38 Set 3/8 x
HSSM The S		MILLER

CORNER CODE

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

## Found Cast Iron Monumonit

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

Fd. Peppetvated Location.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

Found I witness monument. Set 3 witness monuments.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

Steven

I, Lathrep , hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Nav. 14, ZCIZ

CORNER CODE

A.E. 7.08 REQUIREMENT

R-5

SHEET JOF 2.