

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

### CORNER CODE INDEX

FULTON TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B	6					5					4				3					2				1	B
C																									C
D																									D
E																									E
F																									F
G	7					8					9				10					11				12	G
H																									H
J																									J
K																									K
L	18					17					16				15					14				13	L
M																									M
N																									N
O																									O
P	19					20					21				22					23				24	P
Q																									Q
R																									R
S																									S
T	30					29					28				27					26				25	T
U																									U
V																									V
W																									W
X	31					32					33				34					35				36	X
Y																									Y
Z																									Z

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: \_\_\_\_\_

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE V-15

FU608 ^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1836 (AUG) BURNHAM EAST RANDOM BETWN SECS 27 & 34  
5326.2 INT. EAST BOUNDY 11.88' N GOOD 2<sup>ND</sup> RATE W &  
BUR OAK OPENINGS WEST 1/2 BROKEN  
WEST CORRECTED BETWN SECS 27 & 34  
NO STATIONS  
2663.1 SET 1/4 SEC POST W. OAK 24 S60E 1.98' W. OAK 18  
N26W 31.02'  
4759.92 BUR OAK 12 IN DI  
5326.2 TO CORNERS
- 1867 LOCKE VOL 1 PG 282 & #1409 FD BTS & STAKE. 2644.95 TO  
CEN SEC 27 & 5289.9 TO N 1/4 COR SEC 27. {CEN EST. BY  
EQUAL DIST METHOD}
- 1875 RUGER VOL 2 PG 189 & #6571 FD OLD STAKE & BOTH BTS.  
VAR 5-33 ALONG N/S 1/4 LINE SEC 34
- 1877 RUGER VOL 2 PG 229 COR EST. BY SELF SEE SEC 34 PG 144  
VAR 6-00 2657.16 TO CEN SEC 34
- 1965 THORP #1400 CALLS FOR COR BUT STATES NOTHING ABOUT  
MON. MAP SHOWS FENCE INT.
- 1968 THORP #1399 NO MON FOUND (SHOWS FENCE INT.)
- 1974 LEE VOL 5 PG 20 SET CI 2669.90 TO SE COR SEC 27,  
2669.91 TO SW COR SEC 27, 5300.19 TO N 1/4 COR SEC 27,  
ANGLE 90-45-26 @ S 1/4 COR SEC 27 FROM SW TO N 1/4  
CORNERS SEC 27, ANGLE 89-14-34 @ S 1/4 COR SEC 27 FROM  
N 1/4 COR SEC 27 TO SE COR SEC 27
- 1975 NORTHROP CSM VOL 5 PG 18 FD C.I.
- 1976 WOODMAN BK 28-12 FD CI @ 89-13-03 @ CENTER OF SEC 27  
FROM S 1/4 COR SEC 27 TO THE WEST ALONG E/W 1/4 LINE SEC  
27
- 1978 NORTHROP CSM VOL 8 PG 14 & VOL 5 PG 443 FD CI.  
BEARINGS ARE REFERENCED TO TRUE NORTH BY SOLAR  
OBSERVATIONS MADE ON JUNE 21, 1978. S2-28-49W  
2652.83 TO CEN OF SEC 34 & FROM CEN OF SEC 34 TO S 1/4  
COR SEC 34 S0-37-28W 2643.98
- 1999 COMBS #7548 & 7547 CI. 2639.78 TO CEN SEC 27, 5296.99  
TO S 1/4 COR SEC 34, ANGLE 90-46-25 @ S 1/4 COR SEC 27  
FROM SW SEC 27 TO CEN SEC 27, ANGLE 89-08-20 @ S 1/4  
COR SEC 27 FROM S 1/4 COR SEC 34 TO SW COR SEC 27.

FD CI. MON 8' SOUTH OF E/W FENCE & 7.6' EAST OF N/W FENCE.  
PLACED CARSONITE POST BY MON. & REFERENCED SAME

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?


ACCEPTED FD CI. MON THAT WAS SET BY LEE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

LEE DECLARED CORNER LOST & SET ON STRAIGHT LINE BETWEEN  
SW & SE CORNERS OF SEC 27 AT MID POINT.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal  
  
Barnes

1/19/07

SHEET 1 OF 2

CORNER CODE **V-15**

A.E. 7.08 REQUIREMENT

