Paper weight ______nimum) LAND PUBLIC U.S. SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4N., R. _//_E CORNER CODE INDEX

C D E

PORT	EP_	TWP
ROCK	COUNTY	WI

IF AVAILABLE ROCK COUNTY COORDINATES PERFERRED

East Hor. Datum ____ Vert. Datum __ _____ELLIPS. HT.

----- Elev.

LONGITUTE __ GPS (X) ___ TRAVERSE (X) ___

BASED ON THE FOLLOWING CONTROL:

♦ CORNER	MONUMENT
-----------------	----------

PLACE MONUMENT

(a)

LOCATION ON ABOVE INDEX

WITNESS MONUMENT

BEARINGS ARE BASED ON:

SHEET _ _PAGE # _ SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

P0626

- (B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.
- 1974 LEE VOL 5 PG 38 SET ALUM. MON. & REFERENCED SAME
- 197? LEE VOL 5 PG 467 CALLS FOR LOCAL COORDINATES TO THE NEAREST FOOT OF OCCUPATION ON THE NORTH LINE OF SEC 4.
- 1979 BARNES VOL 6 PG 5 CALLS FOR 2620.16 TO THE NE COR SEC 4, 5050.10 TO S 14 COR SEC 4, & AND ANGLE OF 91-13-45 AT N 1/4 COR SEC 4 FROM THE NE COR TO THE S 1/4 COR OF SEC 4.
- 1996 BARNES A-11 FOUND ALUM. MON. & REFERENCE TIES.
- 1997 BARNES PORTER FB #3 PG 52 DUG & FOUND ONLY LIMITS OF OLD EXCAVATION.

AT N 1/4 COR SEC 4 PLACED ALUM. MONUMENT WITH CARSONITE ON WEST SIDE & TWO MAGNETS 18" DEEP. REFERENCED MONUMENTS. N 1/4 COR SEC 4 CENTER TWP IS 23.29' WEST.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

LEE DID NOT STATE WHAT HE FOUND OR HOW HE ESTABLISHED THE CORNER. HIS FIELD NOTES ONLY SHOW THE TIES. I FOUND THE LIMITS OF HIS EXCAVATION. BASED ON MEASURED DISTANCES TO THE WEST & EAST, I BELIEVE HIS ALUM. MONUMENT WAS INCORRECTLY CALLED BY HIM AS THE N 1/4 COR OF SEC 4. I BELIEVE IT IS THE S 1/4 COR SEC 33.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

THE DISCREPANCY WITH THE FOUND PK & FOUND ALUMINUM MONUMENT IS SHOWN.

- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
- I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under by direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

scal

Number of included sheets

emboss

CORNER CODE

A-E 7.08 REQUIREMENT

Donaldbarros FBB, 1999

2-11

