

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

FULTON TWP

ROCK COUNTY WI

IF AVAILABLE

ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B																										B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE X-25

FU620^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1835 BRINK NORTH EAST SIDE SEC 36 T4N R12E VAR FOUND BY
OBSERVATION 7 45'E

969.54 BLACK OAK 12 IN DIAMETER
2640 SET QUARTER SECTION POST BUR OAK 12 N13
1/2W 29.04' BUR OAK 20 S28 1/2W 82.5'
4180.44 BUR OAK 12 IN DIAMETER
5280 SET POST CORNER SECTIONS 25 & 36 BUR
OAK 16 S14W 14.52' BUR OAK N20W 40.92'
LAND ROLLING SECOND RATE BUR WHITE AND
BLACK OAK RED ROOT & C

1867 LOCKE VOL 1 PG 297 & #1482 FD OLD STAKE & REMAINS OF
STUMP OF N. BT. SET STAKE SURROUNDED BY 3 HARDHEADS
VAR 7-50 2627.46 TO CEN SEC 36, VAR 7-20 2659.80 TO NE
COR SEC 36.

1871 (AUG16) RUGER MILTON TWP REMON. NORTH ON WEST LINE
OF SW 1/4 OF SEC 31 ON A VAR 6-20 AT

2656.83 INTERSECTED 1/4 LINE AT 1/4 COR. FOUND STAKE
SURROUNDED BY HARD HEAD STONES AT COR.
ALSO FOUND REMAINS OF STUMPS OF BOTH
BEARING TREES.

NORTH ON WEST LINE OF N.W. 1/4 OF SEC 31
ON A VAR 6-20 AT

2662.66 INTERSECTED NORTH BOUNDARY LINE AT COR.
FOUND HARD HEAD STONE ON COR. ALSO
FOUND WHERE THE STUMPS OF THE 4 BEARING
TREES HAD BEEN DUG OUT
PLACED 6"X6" CUT LIMESTONE

1895 BROWN VOL 2 PG 491 MON. VAR 2-26 2463.45 TO CEN SEC
31 MILTON TWP

1947 SUNNY #1478 CALL FOR COR BUT STATES NOTHING ABOUT
MON. S85W 2630.X TO CENTER OF SEC 36 (SET IRON PIPE
FOR COR, SURROUNDED BY 4 HH), 2651.6X TO SE COR SEC
36 & 2660.X TO NE COR SEC 36

1984 BARNES X-1 FD CUT LIMESTONE 3' DEEP. SET POLY MON. ON
TOP OF STONE & REF. SAME. @ CENTER OF PVMT. & 101.79'
SOUTH OF E/W FENCE. S00-10-01W 2656.74 TO SE COR SEC
36 & N00-10-12E 2665.23 TO NE COR SEC 36

FD POLY & REFERENCE MONUMENTS.

B) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Emboss

Barnes
12/03/07

SHEET 1 OF 1

CORNER CODE **X-25**

A.E. 7.08 REQUIREMENT