

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T.4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3			2			1						B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

FULTON TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: (a) _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 4

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE A-25

FU513^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 (SEP21ST) MULLETT& BRINK EAST ON SOUTH SIDE SECTION 36
T5N R12E
487.08 WHITE OAK 36 IN DIAMETER
2640 SET QUARTER SECTION POST BUR OAK 10 N42E
12.54' BUR OAK 12 N45W 28.38'
4884 TRAIL @ SE
5016 ENTER WILLOW SWAMP
5280 SET POST CORNER TOWNSHIPS 4 & 5N RANGES 12
& 13 E BEARINGS {WILLOW 8 S26E 7.92' BLACK ASH
8 N60W 16.5' MARKED{ WILLOW 8 S72W SWAMP
OAK 12 N57E
- 1833 (OCT 17) MULLETT & BRINK SOUTH BOUNDARY OF 5N R13E 4TH
MER. MT VAR 8-15 EAST ON SOUTH SIDE OF SEC 31
568.26 KOSHONONG LAKE SWAMP OAK TREE 14 IN ??? ON
WEST BANK OF LANK.
LAND LEVEL SECOND RATE AND TIMBERED WITH
WHITE OAK AND SWAMP OAK WHITE MAPLE ELM
BLACK OAK ASPEN HICKORY WILLOW
- 1833 (OCT 17) MULLETT & BRINK VAR 8-15 SOUTH ON EAST SIDE
SECTION 1 T4N R12E
297 LEAVE SWAMP
330 TRAIL @ SE
2640 SET QUARTER SECTION POST WHITE OAK 14 S64W
29.7' WHITE OAK 36 N46W 44.22'
3939.54 WHITE OAK 16 IN DIAMETER
5280 SET POST CORNER SECTIONS 1 & 12 WHITE OAK 26
S10W 41.58' WHITE OAK 14 N72W 34.32' LAND
ROLLING SECOND RATE AND THINLY TIMBERED WITH
WHITE BLACK & BUR OAK HICKORY ?
- 1833 (OCT) MULLETT & BRINK EAST BOUNDARY OF T5N R12E V 7 -
55' NORTH ON EAST SIDE OF SEC 36
875.82 SET MEANDER POST ON WEST BANK OF LAKE
KOSHONONG DOUBLE WHITE MAPLE 40 S39W
27.72' SWAMP OAK 14 S12 1/2E 83.16' LAND LEVEL
3RD RATE W SWAMP OAK LYNN WHITE MAPLE ASPIN
HICKORY ASH & WILLOW VINES OFFSET WEST 2310'
NORTH 8298.18'
- 1871 (SEP11) RUGER MILTON REMON. NORTH ON WEST LINE OF SW
1/4 OF SEC 6 ON A VAR 7-15 OFFSET EAST 6.60' AT
2655.84 INTERSECTED 1/4 LINE 5.28' EAST OF 1/4 COR. FOUND
LARGE STONE AT COR. ALSO FOUND STUMPS OF
BOTH BEARING TREES COR VAR 7-13
NORTH ON WEST LINE OF NW 1/4 OF SEC 6 ON A
VAR 7-15 OFFSET EAST 16.50' AT
2658.48 INTERSECTED NORTH BOUNDARY LINE 40.92' EAST
OF COR. FOUND STUMPS OF BOTH BEARING TREES
& ESTABLISHED COR. FROM THEM. COR VAR 7-47
EAST ON NORTH LINE OF NW 1/4 OF SEC 6 ON A
VAR 6-45 AT
568.26 INTERSECTED MEANDER LINE AT MEANDER COR.
FOUND STUMP OF COR TREE AT COR.
PLACED 6"X6" CUT LIMESTONE
- 1872 GRAVES VOL 6 PG 347 DANE COUNTY SURVEYOR 875.82
FROM SE COR SEC 36 NORTH TO MP ON LAKE KOSKANON
[HIS SPELLING]
- 1880 LEE VOL 2 PG 300 FD STONE MON. 2640 TO S 1/4 COR SEC
36, VAR 4-18 2651.88 TO E 1/4 COR SEC 1.

SHEET 1 OF 4
CORNER CODE A-25

Donald Barnes
OCT 30, 2007

- 1911 HINTZE ALBION T5N R12E REMON. EAST TOWN LINE: FOUND THE SOUTHEAST CORNER OF 36 B. SUMNER'S CORNER; SET MEANDER CORNER 875.8' NORTH, AT SHORE OF LAKE KOSHKONONG. FOUND MEANDER CORNER OF EAST LINE OF SECTION, SET BY SUMNER
SOUTH LINE: SET SOUTH 1/4 OF SEC 36 ON STRAIGHT LINE AND ONE HALF BETWEEN CORNERS. 2635.1 TO SW & SE CORNERS SEC 36. S89-35W FROM SE TO SW CORNERS SEC 36, NORTH FROM SE COR SEC 36 TO MP. AT SE COR SEC 36 ELM 10" N74-15W 27.4'; ELM 6" S79-30E 15'. AT M.P. BR O 10 S82W 12'
AT DANE COUNTY CORNERS, HINTZE INSTALLED CONCRETE MONUMENTS.
THE DIFFERENCE IN BEARING OF LINES BETWEEN SECTION CORNERS GIVES THE TRUE DEVIATION FROM THE STRAIGHT LINE. SOME OF THE BEARINGS ARE MAGNETIC, CHECKED BY MEASUREMENTS, AND THE REST ARE TRANSIT LINES CHECKED BY OBSERVATIONS ON POLARIS. I HEREBY CERTIFY THAT THE DISTANCES AND BEARINGS ARE CORRECT ACCORDING TO SURVEY MADE UNDER THE PROVISIONS OF CHAPTER, 39 SECTION 825 OF THE REVISED STATUTES OF WISCONSIN AND IN ACCORDANCE WITH THE RULES ESTABLISHED BY THE UNITED STATES LAND OFFICE.
- 1958 BATTERMAN VOL 3 PG 572 FD SEC COR TIPPED SOUTH & WEST.
- 1982 BARNES VOL 6 PG 326 FD CUT LIMESTONE, SO-31-10E 2655.62 TO E 1/4 COR SEC 1, S88-39-50W 2646.99 TO N 1/4 COR SEC 1, S88-39-50W 2646.99 TO S 1/4 COR SEC 36. 310,493.38; 2,264,581.86-BARNES, 310,494.42; 2,264,583.10-SANDSNES
- 1982 BARNES A-1 FD CUT L.S. 386' WEST OF WATERS EDGE IN E/W FENCE LINE & N/S FENCE LINE. SET CARSONITE POST. REFERENCED MON IN A-2. 474.22 WEST OF CUT L.S. AT MP IN LAKE KOSHKONONG.
- 1983 BARNES A-2 MP IN LAKE. SAME INFORMATION AS SHOWN ABOVE
- 1983 BARNES REMON. #6794 SO-09-00W 2655.76 TO E 1/4 COR SEC 1.
- 1985 BARNES VOL 6 PG 341 S89-19-23W 2647.28 TO N1/4 COR SEC 1, SO-09-01W 2655.77 TO E 1/4 COR SEC 1, S89-19-23W 2647.28 TO S 1/4 COR SEC 36,
- 1998 SCHROEDER CSM VOL 21 PG 213 CALLS FOR COR. BUT STATES NOTHING ABOUT IT.
- 2004 LORD "WOODLANDS SUBDIVISION" BK32-673 FD L.S. S89-18-07W 1323.46 TO 1/16TH COR. & SOO-09-05W 2655.80 TO E 1/4 COR SEC 1.
- 2005 LORD BK32-720 LS S89-18-07W 2646.92 TO ALUM @ N 1/4 COR SEC 1, ANGLE 89-09-02 @ NE COR SEC 1 FROM E 1/4 COR SEC 1 TO N 1/4 COR SEC 1, & 2655.80 TO ALUM @ E 1/4 COR SEC 1.

FD L.S. /CARSONITE POST. LS IS LEANING. ACCEPTED INT. OF TIE DISTANCES.

SHEET 2 OF 4
CORNER CODE A-25

Donald Barnes
OCT 30, 2007

FU513

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal
Donald Barnes

SHEET 3 OF 4

Emboss

00T 302007

CORNER CODE **A-25**

A.E. 7.08 REQUIREMENT

