

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 12 E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B																									B
C	6																								C
D																									D
E																									E
F																									F
G																									G
H	7																								H
J																									J
K																									K
L	18																								L
M																									M
N																									N
O																									O
P	19																								P
Q																									Q
R																									R
S																									S
T	30																								T
U																									U
V																									V
W																									W
X	31																								X
Y																									Y
Z																									Z

FULTON TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT

○ WITNESS MONUMENT

BEARINGS ARE BASED ON: -----

PLACE MONUMENT SYMBOL ◆ AT PROPER LOCATION ON ABOVE INDEX

FU544^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 (MAR/APR) HARRISON EAST ON RANDOM BET. SECS 8 & 17
2640 TEMPY 1/4 POST
3228.06 WAGON ROAD NE
4113.12 TRAIL NE
4488 LEAVE PRAIRIE & ENTER TIMBER
5323.56 INT. E BDY 18 N OF P LAND GENTLY ROLLING 1ST RATE
PRAIRIE COVERED WITH WILD GRASS & WEEDS
COR WEST BET SEC 8 & 17
2661.78 QUARTER SEC COR {SET POST & RAISED MOUND OF EARTH
& SODS
5323.56 INT SEC COR
- 1844 STEBBINS TWP RD REC BK1 PG 4 SURVEY OF A RD IN THE
TOWN OF FULTON LEADING FROM THE NORTH LINE OF ROCK
COUNTY TO THE INDIAN FORD ON ROCK RIVER MADE APRIL 19TH
1844. BEGINNING AT THE TERMINATION OF A RD LAID IN THE
COUNTY OF DANE AT THE 1/4 POST ON THE SOUTH LINE OF
SOUTH 32 T5N R12E, THENCE S 2 1/2 E 5280' TO 1/4 POST SOUTH
LINE OF S. 5 T4N R12E; THENCE SOUTH 1 EAST 3036' TO STAKE
SET, POST OF BURR OAK, SOUTH 27W 6468', THENCE S32E
4966.5' TO A PT ON THE EAST LINE OF S 17, 662.64' NORTH OF
THE 1/4 POST, THENCE S 1/2 E 3302.64' TO THE SE COR OF S 17 AND
THE WHOLE LENGTH OF THE ROAD IS 16, 585.14'. COURSES GIVEN
ACCORDING TO THE TRUE MERIDIAN. VARIATION OF NEEDLE 7-2
HARRISON STEBBINS CO. SURVEYOR.
- 1871 RUGER VOL 2 PG 57 & #1079 COR LOST. ESTABLISHED IT
FROM SECTION CORNERS. SET LIMESTONE 21X9X5. SAID
STONE IS 30.69' FROM FENCE ON SOUTH SIDE OF ROAD & IN
LINE WITH SMALL MAPLE TREES. 2673.83' VAR 8-02 TO SW COR
SEC 8, 2673.83 VAR 8-02 TO SE COR SEC 8, & VAR 7-58 ALONG N/S
CENTER LINE OF SEC 8.
- 1888/? ROAD RECORDS VOL 6 PG 333 FROM A BOOK IN COUNTY
CLERK'S VAULT SHOWS THE FOLLOWING: STARTING FROM A
POINT ON THE WEST LINE OF SW 1/4 OF SEC 16 WHICH IS 194.06'
FROM THE SW COR SEC 16 & 2445.96 FROM THE W 1/4 COR SEC 16
THENCE N34W 1716', THENCE N55 1/2 W 2024.22 TO THE N 1/4 COR
SEC 17, THENCE NORTH 10,560' TO THE N 1/4 COR SEC 5.
- 1898 BROWN VOL 2 PG 506 & 1078 FD STONE. 2666.73 TO SE COR
SEC 8.
- 1937 SUNNY VOL 3 PG 359 1/4 COR OF SEC 8 & 17 FOUND
LIMESTONE MON AS DESCRIBED BY RUGER 1871. SET 1
1/2"X13" CAPPED PIPE ON TOP. REFERENCED SAME.
- 1964 ELY #1072 & 1073 IRON STAKE FD 2660.70 TO IRON STAKE
DRIVEN AT GEN SEC 8, 2668.55 TO SE COR SEC 8, ANGLE 89-52
@ S 1/4 COR SEC 8 FROM GEN SEC 8 TO SE COR SEC 8
- 1966 BATTERMAN VOL 4 PG 279 REFERENCED CORNER BUT STATES
NOTHING ABOUT MONUMENT. WPL 299,474.75; 2,241,104.83
E/W NAD 27. NOTE: AT S 1/4 COR DUG & FD 2" CAPPED PIPE 4"
DOWN 4/17/72.
- 1972 LEE VOL 4 PG 553 DUG & FD 2" CAPPED PIPE 4" DOWN.
REFERENCED SAME.
- 1975 WPL #1076 299,474.75; 2,241,104.83 S88-40-13W 2677.96
TO SW COR SEC 8 N1-18-11W 2658.99 TO CENTER SEC 8
- 1978 SANDSNES VOL 5 PG 448 299,474.779N/S;
2,241,404.907E/W ELEV 849.30 FOR S 1/4 COR SEC 8 &
299,412.61 N/S; 2,238,427.59 E/W FOR SW COR SEC 8.
- 1978 BARNES VOL 6 PG 42 SHOWS SANDSNES COORDINATES AND
N88-38-41E 2668.16 TO SE COR SEC 8 FROM HIS
COORDINATES. COMPUTED A TRUE NORTH OF N89-15-49E TO SE
COR SEC 8.
- 1980 BARNES VOL 6 PG 42 299,474.78; 2,241,104.91 SANDSNES N88-
38-41E 2668.16 TO SE COR SEC 8.

Daniel Barnes
11/04/07

SHEET 1 OF 2
CORNER CODE J-7(1)

FU544

- 1980 BARNES VOL 6 PG 44 REPLACED CAPPED IRON PIPE. SET ALUM. MON ON TOP OF CUT LIMESTONE THAT WAS 20" DEEP
- 1980 BARNES #9703 ACCIDENT SURVEY STATES NOTHING ABOUT TYPE OF MON. 5315.79 TO S 1/4 COR SEC 5
- 1980 COMBS CSM VOL 9 PL 330 ALUM. MON. 2659.96 TO CEN SEC 8 & ANGLE 89-52-30 @ CEN SEC 8 FROM E 1/4 COR SEC 8 TO S 1/4 COR SEC 8
- 1982 BARNES VOL 6 PG 241. FD ALUM. MON. ELEV 849 & (TRAVERSE SKETCH AS SHOW ON MY SKETCH)
- 1983 BARNES VOL 6 PG 303 BEARINGS & DISTANCES COMPUTED FROM RECORD COORDINATES. N88-38-39E 2668.24 TO SE COR SEC 8, S88-40-13W 2677.96 TO SW COR SEC 8, N1-18-11W 2658.99 TO CENTER OF SEC 8. WPL 299,474.75N/S; 2,241,104.83 E/W, ROYAL OAK ENGINEERING 299,474.78 N/S; 2,241,104.91E/W
- 1999 BARNES J-7 FD ALUM. MON. & SOME OF THE REFERENCE MONUMENTS. ESTABLISHED COUNTY COORDINATES FROM WPL GPS STATIONS. 318,414.41N/S; 472,142.90 E/W ACCEPTED FOUND ALUM. MON.

FD ALUM. MON. & REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal



Emboss

11/04/07

SHEET 2 OF 2

CORNER CODE **J-7(1)**

A-E 7.08 REQUIREMENT