

PLAT AND RECORD

VOL. 6

Of a Survey on Section 32 T 5 R 12 E. of the 4 P. M. in ALBION Township

Rock County, Wisconsin, made JUNE the 20 19 1866

I hereby certify that the following is a correct record of said survey as made by me.

COUNTY BUILDING
CITY OF JANESVILLE

H.M. WARNER DANE COUNTY SURVEYOR
County Surveyor.

COPIED FROM DANE COUNTY SURVEYOR'S RECORDS BOOK 6 PAGE 280 2/17/86

MICROFILMED



SURVEYED THE ABOVE PLATTED SECTION AS ABOVE REPRESENTED AND ESTABLISHED THE NORTH EAST CORNER OF THE SAID SECTION BY TAKING EQUAL FROM THE 1/4 POST NORTH & SOUTH AND THE PROPORTIONATE QUARTER POST WEST AND THE NEAREST ESTABLISHED GOVERNMENT POST TO BE FOUND ON THE EAST AND SET STONES FOR CORNER AT THE SAID NORTH EAST CORNER AT THE EAST, NORTH, AND SOUTH QUARTER CORNERS AND AT 8, 9, AND 16.

DONE JUNE 20th 1866

H.W. WARNER COUNTY SURVEYOR

NOTES ??76 SEE BOOK CW3 p 19 & 29

SURVEYED THE W 1/2 OF SEC 32 FROM GOVERNMENT AND WARNERS CORS. DEC 27 1867 ESTABLISHED CORNERS AS ABOVE PLATTED WITH BEARING TREES AS FOLLOWS:
 AND OAK STUMP 2ft N60°W56 lks) RIGHT BY U.S.B.T.S
 AT (2) BL OAK 6in S 64°W 126 lks) AT N.W. COR STONE SET) AT (4) BL OAK 7 in S18°E 21 lks. STAKE AND STONE SET FOR COR EAST SIDE RD CENTER OF N & S ROAD AND STONE SET CENTER OF ROAD
 AT (5) BL OAK 5 in S18°W 109 1/2 lks) AT (9) stone SET BY WARNER AT (a) BL OAK 6 in N20 1/2 W 152 1/2 lks AND POPLAR 5 in N 45E 26 LKS
 AT (10) BL OAK 4 in S35E24 1/2 LKS AT (b) BL OAK STUMP 12in N84°E 124 1/2 lks AND STAKE
 W 1/4 S FOUND BY US.B.T.S BOTH STANDING.

CHAS H BARTON
COUNTY SURVEYOR