

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 14 E.

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B																									B
C																									C
D																									D
E																									E
F																									F
G																									G
H																									H
J																									J
K																									K
L																									L
M																									M
N																									N
O																									O
P																									P
Q																									Q
R																									R
S																									S
T																									T
U																									U
V																									V
W																									W
X																									X
Y																									Y
Z																									Z

LIMA TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.
PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE V-7 (3)

LI604

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1973 LEE VOL 5 PG 25 DOES NOT DESCRIBE MONUMENT.

PLACED TIES AND CALLED FOR MONUMENT SOUTH OF CENTER PAVEMENT, 10 EAST OF N/S FENCE ON NORTH SIDE OF RD

1982 BARNES V-7 FOUND OLD REFERENCE MONUMENTS PLACED PK FROM TIES. PK WAS 8.3' SOUTH OF CENTER OF PVMT.

CORNER WILL BE DESTROYED BY NEXT YEAR'S CONSTRUCTION.

1982 BARNES TOWNSHIP PROJECT. FOUND DOT PI STATIONS

216+38.86 & 253+84.14 & OCCUPIED 253+84.14 & USED

216+38.86 AS THE BACKSIGHT. MEASURED ANGLE AND

DISTANCE TO A PK AT THE S ¼ COR OF SEC 29. USED LEAST

SQUARES COORDINATE TRANSFORMATION PROGRAM AND

COMPUTED 283,364.37; 2,301,452.14. CALLED FOR 2648.27

TO SW COR SEC 29 & 2649.33 TO SE COR SEC 29. PK WILL BE

DESTROYED WITHIN A YEAR.

1983 WIDOT 6TH59 R/W PLANS PROJECT #3143-00-21 SHEET

#4.10 PK NAIL, 283,314.53; 2,304,099.63 8.34'

PERPENDICULAR TO REF. LINE AT STA 273+77.58 N1-10-26E

1985 WIDOT V-7(1) FOUND ½ SCREW & RIBBON. 8.34'

PERPENDICULAR TO REF LINE (RT) 273+77.58. SURFACE MON.

WILL BE DESTROYED WITHIN A YEAR

1992 BARNES V-7(2) PLACED SMALL R/R SPIKE. FD ONE 1973

BENT REFERENCE PIPE. USED THIS AND WIDOT REFERENCE

RODS TO SET RR/ SPIKE ACCEPTED OBLITERATED EVIDENCE

LOCATION. USED RECORD DISTANCE TO THE NW REFERENCE

TIE, DOT REFERENCE LINE INFORMATION, NEW AND OLD TWP

TRAVERSE BETWEEN THE SW LINE OF SECTION 31 AND

STATIONS NEAR THE SE CORNER OF SECTION 29 TO COMPUTE

THE POSITION BY LEAST SQUARES. REFERENCED CORNER.

COR 9.2' SOUTH OF CENTER PVMT.

IN THE FALL OF 2001 FD R/R & DOT REFERENCE PINS. R/R WILL BE DESTROYED WITH IN A FEW MONTHS. IN APR 2002 FD R/R & REFERENCE MONUMENTS. SET STEEL SURVEY SPIKE STAMPED "SURVEY MARK" FROM TIES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald Barnes
Emboss

5/31/02

SHEET 1 OF 2

CORNER CODE V-7(3)

A.E. 7.08 REQUIREMENT

